



PRODUCT-DETAILS

# UPS PowerValue 11RT G2 2 kVA B

## UPS PowerValue 11RT G2 2 kVA B

### General Information

Extended Product Type	UPS PowerValue 11RT G2 2 kVA B
Product ID	4NWP100201R0001
EAN	7640169263033
Catalog Description	UPS PowerValue 11RT G2 2 kVA B
Long Description	VFI UPS PowerValue 11 RT 2000VA/2000W ; 230V; 50/60Hz; 4 min

### Additional Information

Apparent Power Output	2000 V·A
Battery Chemical Composition	Lead-Acid
Battery Runtime	4 minute [unit of time]
Battery Type	Portable
Battery Weight	2.5 kg
CN8	85044000
Communication Interface	USB RS-232
Communication Protocol and Connection	SNMP
Connection Type	IEC C20
Country of Origin	China (CN)
Customs Tariff Number	85044000
Data Sheet, Technical Information	4NWD002979_EN
Declaration of Conformity - CE	4NWD005356
E-Number (Finland)	8408637
EAN	7640169263033
ETIM 6	EC000382 - UPS
ETIM 7	EC000382 - UPS
Efficiency	Overall 91 % Economy Mode (Eco-Mode) 98 %
Harmonic Distortion	2.00 %
Input Voltage (U <sub>in</sub> )	208 V 220 V 230 V 240 V
Input Voltage Type	AC
Instructions and Manuals	4NWD005357

Invoice Description	UPS PowerValue 11RT G2 2 kVA B
Minimum Order Quantity	1 piece
Number of Batteries	3
Number of Outputs	C13 Connection 8
Number of Phases	Primary - 1 Secondary - 1
Object Classification Code	G
Options Provided	Auto shut down function Potential free switch contact Network-management
Output Voltage (U <sub>out</sub> )	208 V 220 V 230 V 240 V
Package Level 1 Depth / Length	560 mm
Package Level 1 EAN	7640169263033
Package Level 1 Gross Weight	21.1 kg
Package Level 1 Height	180 mm
Package Level 1 Units	1 piece
Package Level 1 Width	500 mm
Power Factor	1.0
Product Main Type	PowerValue 11RT G2
Product Name	UPS
Product Net Depth / Length	427 mm
Product Net Height	86 mm
Product Net Weight	19.1 kg
Product Net Width	438 mm
REACH Declaration	4NWD005391
Rated Frequency (f)	Primary 50 Hz Primary 60 Hz Secondary 50 Hz Secondary 60 Hz
Rated Output Power	1000 W
RoHS Date	0320
RoHS Information	4NWD005356
RoHS Status	Following EU Directive 2011/65/EU
Selling Unit of Measure	piece
Uninterruptible Power Supply Form Factor	Rack-Tower
Uninterruptible Power Supply Topology	On-Line Double Conversion
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)