

# Mallia™ push-buttons, dimmers, automatic switches and other lighting functions - customisable colours

**NEW**



2 830 84



2 834 90



2 832 81



2 812 75

Plate selection charts **p. 36-37**

Conform to BS EN 60669 – 1  
 Painted polycarbonate front cover  
 Compact mechanism for a larger wiring space  
 Supplied with 2 screws M 3.5 for BS boxes  
 To be equipped with plates - Dim.: 86 x 86 mm

## Pack Cat.Nos Push-buttons 10 A - 250 V~

Pack	Cat.Nos	Description
5	2 830 41	<b>N/O contact (push to make)</b> ● Silver ● Pearl ● Dark Silver
5	2 832 41	
5	2 834 41	
5	2 830 40	<b>N/O contact with bell symbol</b> ● Silver ● Pearl ● Dark Silver
5	2 832 40	
5	2 834 40	

## Dimmers

Pack	Cat.Nos	Description
1	2 830 80	<b>Rotary control dimmer</b> 60-500 W for incandescent and halogen lamps 230 V~ 60-300 VA ELV halogen lamps with ferromagnetic transformer and compensator Cat.No 0 401 39 ● Silver ● Pearl ● Dark Silver
1	2 832 80	
1	2 834 80	
1	2 830 84	<b>Rotary control dimmer + switch</b> 500 W rotary control dimmer + 2-way switch - for incandescent and halogen lamps 230 V~ ● Silver ● Pearl ● Dark Silver
1	2 832 84	
1	2 834 84	
1	2 830 85	<b>Rotary dimmer</b> 60-1000 W for incandescent and halogen lamps 230 V 60-1000 VA for halogen lamps with ferromagnetic transformers Can control electronic transformers with leading edge behaviour, max. 600 VA Installation without neutral ● Silver ● Pearl ● Dark Silver
1	2 832 85	
1	2 834 85	

## Automatic switches

Pack	Cat.Nos	Description
1	2 830 90	<b>IR movement detector</b> Horizontal detection angle 180° Luminosity threshold: 43 to 1614 lux Temporization: 20 s - 15 min Detection range: max. 12 m Compatible load: 25 - 200 W for incandescent and halogen lamps 230 V~ ● Silver ● Pearl ● Dark Silver
1	2 832 90	
1	2 834 90	

## Pack Cat.Nos Programmable switches

Pack	Cat.Nos	Description
1	2 830 92	Power supply: 230 V~ - 50/60 Hz Maximum load: 2300 W Weekly programme Capacity: max. 28 programmes Output: 1 changeover contact ● Silver ● Pearl ● Dark Silver
1	2 832 92	
1	2 834 92	

## Time delay switches

Pack	Cat.Nos	Description
1	2 830 91	Adjustable time from 5 min to 12 h Maximum load: 500 W incandescent and halogen lamps 230 V~ 250 W fluorescent lamps without capacitor ● Silver ● Pearl ● Dark Silver
1	2 832 91	
1	2 834 91	

## Fan speed controls

Pack	Cat.Nos	Description
1	2 830 81	<b>400 VA rotary fan controls</b> ● Silver ● Pearl ● Dark Silver
1	2 832 81	
1	2 834 81	
1	2 830 82	<b>5-speed fan controls</b> 100 W for fan with overall diameter 48" ● Silver ● Pearl ● Dark Silver
1	2 832 82	
1	2 834 82	

## Cooker control units 45 A - 250 V~

Pack	Cat.Nos	Description
5	2 812 75	Supplied complete with plate Conform to BS 4177 45 A DP switch + 13 A switched socket outlet with red indicator Dim.: 146 x 86 mm ● Silver ● Pearl ● Dark Silver
5	2 832 75	
5	2 834 75	