Product sheet



BELANKO S LEGRAND

Belanko S - 2 gang single pole BS switched socket outlet inboard rockers - 13A - Ivory

REF. 617846 | EAN. 3414971689787

> Visit e-catalogue

Product charateristics

- 2p+E British Standard, 13A, 250V
- Sold with white BELANKO S plate
- Screw type terminals for a secured & enhanced contacts
- Marked terminals for easy identification
- Switch allows safe disconnection of an electrical appliance

Recommendations / Restrictions

- Recommended inside use only

The product's benefits

Installation

- Quick & Easy plate clipping system

Usage

- Fitted with safety shutters to maximise child protection

Advantages

- Delivered with its protective shell against paint and dust during installation phase
- Optimised range for new builds and ideal for renovation projects
- Delivered with screws for flush & surface boxes in both plastic and metal boxes

Technical characteristics

Model	British Standard
Concurrently switching neutral conductor	No
Protective contact	Flat
Number of active contacts (round)	0
Number of active contacts (flat)	4
Number of active contacts (square)	0
Assembly arrangement	Basic element with full cover plate

Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With on/off switch	Yes
Nominal current	13 A

With complemantary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of socket outlets	2
Number of modules (module system)	4
Number of socket outlets switchable	2
Number of phases	1
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	Yes
Colour	Beige
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Mounting with screw
Material	Plastic

Nominal voltage	250 V
Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04
Device width	146 mm
Device height	86 mm
Device depth	29.5 mm
Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
Built-in depth	18.4 mm
Operating / setting temperature (Min-Max)	-5-50 °C
Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Power Delivery	No
Terminal marking indication	Yes
Prewired	No
Terminals capacity (Min-Max)	1-4 mm^2
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	1-4 mm^2
Cable support	Not applicable
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

F02973EN-01.pdf | PDF (0.52Mo)

Agreements & Certificates

G-MARK-0048-1539 | (0.58Mo)

OC / CB-SE-90908M1 | (1.02Mo)

OC / CB-FR_719315 | (0.61Mo)

OC / CB-CN48885-M1 | (0.61Mo)

AoC-N°2566AS03ARLI58973 | (0.32Mo)

LGRP-00925-V02.01-EN.pdf | PDF (0.72Mo)