Product sheet



SYNERGY™ LEGRAND

Synergy™ - Double pole socket outlet - 2 gang - 13 A 250 V~ - White

REF. 730070 | EAN. 3245067300701

> Visit e-catalogue

Product charateristics

- Synergy - British standard socket outlets - white - Front plates : white thermoset - Terminal screws captive and backed off ready for cabling - large angled terminal entries - Compact mechanism for maximised wiring space - Supplied with faceplate screw caps
- Double pole socket outlets 13 A - 250 V~ - Conform to BS 1363 : Part. 2 - With safety shutter mechanism - For flush-mounting, back box to be min. 25 mm deep - ASTA licence Switched - 2 gang - Nominal plate dimensions : 86 x 146 mm

Technical characteristics

Model	British Standard
Concurrently switching neutral conductor	Yes
Protective contact	Flat
Number of active contacts (round)	0
Number of active contacts (flat)	4
Number of active contacts (square)	0
Assembly arrangement	Basic element with full cover plate
With complemantary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of socket outlets	2
Number of modules (module system)	4
Number of socket outlets switchable	2
Number of phases	1
Imprint/indication	Other

Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	Yes
Rotated central insert	No
Nominal current	13 A
Nominal voltage	250 V
Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP2X
degree of impact strength (IK)	IK01
Device width	146 mm

Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No
Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Mounting with screw

Device height	86 mm
Device depth	30 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	19.5 mm
Operating / setting temperature (Min-Max)	-5-40 °C
Storage temperature (Min-Max)	-5-40 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	4-4 mm^2
Cable support	Other
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

F00167EN-00.pdf | PDF (0.34Mo)

Agreements & Certificates

G-MARK-0048-1240 R 1 | (1.99Mo)

ASTA-780 | (0.28Mo)

LGRP-2013-234-V1-EN.pdf | PDF (1.02Mo)

AoC-2566AS04ARLI59414 | (0.37Mo)

OC / CB-FR_70445/A1 | (0.54Mo)