Product sheet



SYNERGY™ SLEEK LEGRAND

Synergy™ Sleek - 1 gang switched single pole socket outlet 15A - Brushed Stainless Steel

REF. 832089 | EAN. 3414970661128

> Visit e-catalogue

Product charateristics

- BRITISH STANDARD 15A 250V~
- Type M 2P+E three round pins socket conform to BS546
- Screwless cover plate is square 86x86 mm,product thickness is 4mm (once is installed onto the wall).
- Complete product, cover plates are clipped onto the mechanism itself.

Recommendations / Restrictions

- Recommended inside use only

The product's benefits

Installation

- Strip length indicator avoids waste of wires.Terminal screws backed off ready to cabling

Advantages

- Plate and switch rocker in same metal: austenitic stainless steel Non magnetic Grade 304L
- Made in UK
- Delivered with screws for flush & surface boxes in both plastic and metal boxes

Technical characteristics

Model	British Standard
Concurrently switching neutral conductor	No
Protective contact	Round
Number of active contacts (round)	2
Number of active contacts (flat)	0
Number of active contacts (square)	0
Assembly arrangement	Basic element with full cover plate
With complemantary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0

Material	Metal
Material quality	Stainless steel
Halogen free	Yes
Surface protection	Metallic
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	Yes
Rotated central insert	No
Nominal current	15 A

Number of socket outlets	1
Socket outlets phase-separated	No
Number of modules (module system)	2
Number of socket outlets switchable	1
Number of phases	1
Imprint/indication	Other
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	No
Label space/information surface	No
Colour	Stainless steel
Metallic colour	Yes
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Mounting with screw

Nominal voltage	250 V
Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP2X
degree of impact strength (IK)	IK01
Device width	86 mm
Device height	86 mm
Device depth	36 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	29 mm
Operating / setting temperature (Min-Max)	-5-40 °C
Storage temperature (Min-Max)	-5-40 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	6-6 mm^2
Cable support	Other
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

F02268EN-00.pdf | PDF (0.66Mo)