Product sheet



SYNERGY™ SLEEK LEGRAND

Synergy™ Sleek - Unswitched Fused Connection Unit with cord outlet - Glossy Gold

REF. 832432 | EAN. 3414970663023

> Visit e-catalogue

Product charateristics

- 13A, 250V~
- Cord outlet allows the connection of an external device
- Screw type terminals for enhanced contacts accept wires up to 2X6mm2
- Screwless cover plate is square 86x86 mm,product thickness is 4mm (once is installed onto the wall).
- Complete product, cover plates are clipped onto the mechanism itself.

Recommendations / Restrictions

- Recommended inside use only

The product's benefits

Installation

- Compact mechanisms for maximum wiringspace (back box to be min. 25mm) and slim front plates

Usage

- Fused supplied, locked captive fuse carrier (padlockable)

Advantages

- Plate is made in Stainless Steel - Grade 430, with a chromium plating which bring a better rusting resistance and a nicer finish
- Made in UK
- Delivered with screws for flush & surface boxes in both plastic and metal boxes

Technical characteristics

Connection type	Screw connection
Mounting method	Front mounting
Type of current	AC
Rated current	13 A
Rated voltage	250 V
Dimensions glass fuse	5x25 mm
Width	86 mm

Depth	29 mm
Built-in depth	22 mm
degree of impact strength (IK)	IK01
Degree of protection (IP)	IP20
Operating / setting temperature (Min-Max)	-5-40 °C
Storage temperature (Min-Max)	-5-40 °C
Cable section (Min-Max)	6-6 mm^2

Height	86 mm

Documentation

TECHNICAL DOCUMENTATION

F02656EN-00.pdf | PDF (0.1Mo)

Agreements & Certificates

ASTA-880 | (0.35Mo)