Product sheet



SYNERGY™ METALCLAD LEGRAND

Synergy Double Pole Fused Connection Unit unswitched + cord outlet 13A - Metalclad

REF. 733836 | EAN. 3245067338360

Synergy Fused connection unit conform to BS 1363, front cable outlet with cord grip, locked captive fuse carrier (padlockable), for flush-mounting, back box to be minimum 25mm deep. Nominal plate dimensions : 86x86mm

> Visit e-catalogue

Description

Synergy Fused connection unit conform to BS 1363, front cable outlet with cord grip, locked captive fuse carrier (padlockable), for flush-mounting, back box to be minimum 25mm deep. Nominal plate dimensions : 86x86mm

Product charateristics

- Synergy - British standard socket outlets and fused connection units - Metalclad - Front plates : grey epoxy coated steel - Terminal screws captive and backed off ready for cabling - large angled terminal entries - Supplied complete with close fit 43 mm deep surface - mounting back box
- Fused connection units 13 A - 250 V~ - Conform to BS 1363 - Part 4 : 1995 - Fused 13 A (fuse supplied) - Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety - Flush-mounting back box : min. 25 mm deep - Nominal plate dimensions : 86 x 86 mm Double pole switched - With cord outlet

Technical characteristics

Connection type	Screw connection
Mounting method	Front mounting
Type of current	AC
Rated current	13 A
Rated voltage	230 V
Dimensions glass fuse	5x25 mm
Width	86 mm

Height	86 mm
Depth	44 mm
degree of impact strength (IK)	IK01
Degree of protection (IP)	IP20
Operating / setting temperature (Min-Max)	-5-40 °C
Storage temperature (Min-Max)	-5-40 °C
Cable section (Min-Max)	6-6 mm^2

Documentation

TECHNICAL DOCUMENTATION

F02518EN-00.pdf | PDF (0.08Mo)

Agreements & Certificates

ASTA-880 | (0.35Mo)