Product sheet



GALION™ LEGRAND

Galion Fused Connection Unit switched with RED LED 13A - White

REF. 282453 | EAN. 3414971855434

Fused connection unit allows the electrical protection of the device connected to it (possible from the front via a hole), and its control with a switch.

> Visit e-catalogue

Description

Fused connection unit allows the electrical protection of the device connected to it (possible from the front via a hole), and its control with a switch.

Product charateristics

- 13A, 250V~
- Sold complete under one catalog number, ready to install.
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Strip length indicator avoids waste of wires

Recommendations / Restrictions

- Product delivered with paint and dust protection
- Delivered with screws for flush-mounting or surface-mounting boxes, plastic or metal

The product benefits

Installation

- Honeycomb design supporting frame for stability and rigidity

Technical characteristics

Mounting method	Surface mounted/recessed mounted
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Colour	White
Suitable for degree of protection (IP)	IP20
Device width	86 mm

Device height	88 mm
Device depth	34.5 mm
Built-in depth	22.4 mm
degree of impact strength (IK)	IK04
Operating / setting temperature (Min-Max)	-5-50 °C
Storage temperature (Min-Max)	-10-70 °C
Antimicrobial treatment	No

Documentation

TECHNICAL DOCUMENTATION

F02867EN-00 Fused connection unit.pdf | PDF (0.82Mo)

Agreements & Certificates

AoC-TA24-0515 | (0.32Mo)