
Product sheet



GALION™ LEGRAND

Galion Fused Connection Unit unswitched + cord outlet 13A - Matt black

REF. 282450-C | EAN. 3414971855342

Fused connection unit allows the electrical protection of the device connected to it

> Visit e-catalogue

Description

Fused connection unit allows the electrical protection of the device connected to it

Product charateristics

- 13A, 250V~
- Sold complete under one catalog number, ready to install.
- Screw type terminals for enhanced contacts
- Marked terminals for easy identification
- Strip length indicator avoids waste of wires

Recommendations / Restrictions

- Product delivered with paint and dust protection
- Delivered with screws for flush-mounting or surface-mounting boxes, plastic or metal

The product benefits

Installation

- Honeycomb design supporting frame for stability and rigidity

Technical characteristics

Connection type	Screw connection
Mounting method	Other
Type of current	AC
Rated current	13 A
Rated voltage	250 V
Dimensions glass fuse	5x25 mm
Width	86 mm
Height	88 mm
Depth	31.1 mm

Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz
Mandatory neutral	No
Terminal marking indication	Yes
Colour	Black
Halogen free	Yes
Antimicrobial treatment	No
Number of terminals	5

Built-in depth	21.6 mm
degree of impact strength (IK)	IK04
Degree of protection (IP)	IP20
Operating / setting temperature (Min-Max)	-5-50 °C

Terminals capacity (Min-Max)	1-4 mm^2
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	1-4 mm^2

Documentation

Agreements & Certificates

AoC-TA24-0515 | (0.32Mo)