Product sheet



GALION™ LEGRAND

Galion British Standard switched socket outlet - 5A - 1 gang - Matt black

REF. 282438-C | EAN. 3414971854970

The switched single pole socket outlet allows the connection and the control of an electrical or electronic device requiring a supply of 5A.

> Visit e-catalogue

Description

The switched single pole socket outlet allows the connection and the control of an electrical or electronic device requiring a supply of 5A.

Product charateristics

- 2P+E British Standard, 5A, 250V~
- Sold complete under one catalog number, ready to install.
- Screw type terminals for secure and enhanced contacts
- Marked terminals for easy identification
- Strip length indicator avoids waste of wires

Recommendations / Restrictions

- Product delivered with paint and dust protection
- Delivered with screws for flush-mounting or surface-mounting boxes, plastic or metal

The product benefits

Installation

- Honeycomb design supporting frame for stability and rigidity

Usage

- Fitted with safety shutters to maximise child protection

Technical characteristics

Model	British Standard
Concurrently switching neutral conductor	No
Protective contact	Round
Number of active contacts (round)	2
Number of active contacts (flat)	0
Number of active contacts (square)	0
Assembly arrangement	Basic element with full cover plate
With complemantary luminous signal	No
Number of ports USB-A	0

Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Lacquered
Surface finishing	Matt
Antimicrobial treatment	No
With on/off switch	Yes
Colour of switch operator	Black
Nominal current	5 A

Number of ports USB-C	0
Number of socket outlets	1
Socket outlets phase-separated	No
Number of modules (module system)	2
Number of socket outlets switchable	1
Number of phases	1
Imprint/indication	Scanable symbol/barrier free
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Colour	Black
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	Yes
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Mounting with screw

Nominal voltage	250 V
Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP20
degree of impact strength (IK)	IK04
Device width	86 mm
Device height	88 mm
Device depth	29.9 mm
Min. depth of built-in installation box	35 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
Built-in depth	18.2 mm
Operating / setting temperature (Min-Max)	-5-50 °C
Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Power Delivery	No
Terminal marking indication	Yes
Terminals capacity (Min-Max)	1-4 mm^2
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	1-4 mm^2
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

F02860EN-00 15A&5A switch socket.pdf | PDF (0.67Mo)

Agreements & Certificates

OC / CB-FR-707113/M3 | (0.59Mo)

LGRP-02060-V01.01-EN.pdf | PDF (0.72Mo)

G-MARK-0032-1861-V-1 | (13.62Mo)