# Product sheet




GALION™ LEGRAND

## Galion Multistandard switched socket outlet - 1 gang 2P+E - Matt Black

REF. 282434-C | EAN. 3414971854857

The single multistandard switched socket allows the connection of an electrical device to power it whatever the plug standard

> Visit e-catalogue

## Description

The single multistandard switched socket allows the connection of an electrical device to power it whatever the plug standard

### Product charateristics

- 2P+E Multi standard, 15A, 127V~- 16A, 250V~
- Sold complete under one catalog number, ready to install.
- Screw type terminals for secure and enhanced contacts
- Marked terminals for easy identification
- Strip length indicator avoids waste of wires

### Recommendations / Restrictions

- Product delivered with paint and dust protection
- Delivered with screws for flush-mounting or surface-mounting boxes, plastic or metal

## The product benefits

### Installation

- Honeycomb design supporting frame for stability and rigidity

### Usage

- Fitted with safety shutters to maximise child protection

## Technical characteristics

| | |
|---|---|
| **Model** | Multi-standard socket |
| **Protective contact** | Other |
| **Assembly arrangement** | Basic element with full cover plate |
| **With complemantary luminous signal** | No |
| **Number of ports USB-A** | 0 |
| **Number of ports USB-C** | 0 |
| **Number of socket outlets switchable** | 1 |
| **Number of phases** | 2 |
| **Imprint/indication** | Scanable symbol/barrier free |

| | |
|---|---|
| **Surface protection** | Lacquered |
| **Surface finishing** | Matt |
| **Antimicrobial treatment** | No |
| **With on/off switch** | Yes |
| **Nominal current** | 16 A |
| **Nominal voltage** | 250 V |
| **Frequency (Min-Max)** | 50-60 Hz |
| **Suitable for degree of protection (IP)** | IP20 |
| **degree of impact strength (IK)** | IK04 |

| | |
|---|---|
| **Connection type** | Screwed terminal |
| **With hinged lid** | No |
| **With enhanced contact protection** | Yes |
| **Colour** | Black |
| **Metallic colour** | No |
| **Transparent** | No |
| **Lockable** | No |
| **Eject-mechanism** | Yes |
| **Insulated mounting** | No |
| **With function lighting** | No |
| **With orientation lighting** | No |
| **Overvoltage protection** | No |
| **Fault current protection** | No |
| **With miniature fuse** | No |
| **Special power supply** | None |
| **Mounting method** | Flush-mounted |
| **Type of fastening** | Mounting with screw |
| **Material** | Plastic |
| **Material quality** | Thermoplastic |
| **Halogen free** | Yes |

| | |
|---|---|
| **Device width** | 86 mm |
| **Device height** | 88 mm |
| **Device depth** | 41.2 mm |
| **Min. depth of built-in installation box** | 35 mm |
| **Compatible with Apple HomeKit** | No |
| **Compatible with Amazon Alexa** | No |
| **Compatible with Google Assistant** | No |
| **IFTTT support available** | No |
| **With Wi-Fi signal repeater** | No |
| **With built-in bluetooth speaker** | No |
| **Built-in depth** | 29.3 mm |
| **Operating / setting temperature (Min-Max)** | -5-50 °C |
| **Storage temperature (Min-Max)** | -10-70 °C |
| **Voltage type** | AC |
| **Power Delivery** | No |
| **Terminal marking indication** | Yes |
| **Terminals capacity (Min-Max)** | 1-4 $mm^2$ |
| **Cable nature for connection** | Flexible or rigid |
| **Cable section (Min-Max)** | 1-4 $mm^2$ |
| **Connected object** | No |

## Documentation

### TECHNICAL DOCUMENTATION

F02869EN-00 MULTISTD SWITCHED SOCKETS.pdf | PDF (0.67Mo)

### Agreements & Certificates

LGRP-02060-V01.01-EN.pdf | PDF (0.72Mo)