
Product sheet



ARTEOR LEGRAND

Arteor British Standard Single Pole Socket Outlet 13A 2P+E switched and shuttered - 2 Gang - White

REF. 572145 | EAN. 3245065721454

Arteor - British standard socket outlets Single pole socket outlets - Shuttered for child safety

> Visit e-catalogue

Description

Arteor - British standard socket outlets Single pole socket outlets - Shuttered for child safety

Product charateristics

- Arteor™ - British standard socket outlets- Mechanisms supplied with rocker plates, to be equipped with special plates- Support frame not needed
- Single pole socket outlets 13 A - 250 V~- Shuttered for child safety- ASTA licence- Conform to BS 1363 Part 2- Use special plates2P+E switched - 2 gang - White

Technical characteristics

Model	British Standard
Concurrently switching neutral conductor	No
Protective contact	Flat
Number of active contacts (round)	0
Number of active contacts (flat)	4
Number of active contacts (square)	0
Assembly arrangement	Basic element with full cover plate
With complemantary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of socket outlets	2
Number of modules (module system)	4
Number of socket outlets switchable	2

Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	Yes
Colour of switch operator	White
Rotated central insert	No
Nominal current	13 A
Nominal voltage	250 V
Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP20

Number of phases	1
Imprint/indication	Other
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No
Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Mounting with screw
Material	Plastic

degree of impact strength (IK)	IK04
Device width	143.5 mm
Device height	83.5 mm
Device depth	19.9 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	30.95 mm
Operating / setting temperature (Min-Max)	-5-50 °C
Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	4-4 mm^2
Cable support	Other
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

- F03658FR-01.pdf | PDF (0.5Mo)
- F03658EN-01.pdf | PDF (0.52Mo)

Agreements & Certificates

- ASTA-1068 | (0.34Mo)
- G-MARK-0048-1614 | (1.18Mo)
- OC / CB-FR_707461/M1 | (0.54Mo)
- LGRP-01581-V01.01-EN.pdf | PDF (0.5Mo)
- AoC-N°2566AS09ARLI62427 | (0.31Mo)