Product sheet



ARTEOR LEGRAND

Arteor British Standard Unswitched Socket Outlet 5A - 2P+E - 2 Module - White

REF. 572110 | EAN. 3245065721102

Arteor - international socket outlets - Shuttered for child safety

> Visit e-catalogue

Description

Arteor - international socket outlets - Shuttered for child safety

Product charateristics

- Arteor™ - international socket outlets- Mechanisms supplied with rocker plates, to be equipped with support frames and plates
- British standard socket outlets- Shuttered for child safety- ASTA licence- Conform to BS 1363 Part 2- Use special plates2P+E - 5 A- Conform to BS 546- 2 modules - White

Technical characteristics

Model	British Standard
Concurrently switching neutral conductor	No
Protective contact	Round
Number of active contacts (round)	2
Number of active contacts (flat)	0
Number of active contacts (square)	0
Assembly arrangement	Basic element with full cover plate
With complemantary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of socket outlets	1
Socket outlets phase-separated	No
Number of modules (module system)	2

Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	No
Colour of switch operator	White
Rotated central insert	No
Nominal current	5 A
Nominal voltage	250 V
Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP40

Number of socket outlets switchable	0
Number of phases	1
Imprint/indication	Other
Connection type	Screwed terminal
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No
Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Module frame
Type of fastening	Snap mounting (engagement)

degree of impact strength (IK)	IK04
Device width	45 mm
Device height	45 mm
Device depth	31.6 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	23.1 mm
Operating / setting temperature (Min-Max)	-5-50 °C
Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	4-4 mm^2
Cable support	Other
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

F00723EN-05.pdf | PDF (1.07Mo)

F00723FR-05.pdf | PDF (1.07Mo)