Product sheet



ARTEOR LEGRAND

Arteor Double USB sockets 15W- 2xType A - 2 Module - Magnesium

REF. 572578 | EAN. 3245065725780

Arteor USB charging sockets - square version USB power supplies - For recharging portable devices

> Visit e-catalogue

Description

Arteor USB charging sockets - square version USB power supplies - For recharging portable devices

Product charateristics

- Arteor™ USB charging sockets - square version- Mechanisms supplied with rocker plates, to be equipped with support frames and plates
- USB power supplies- For recharging portable devices- Conform to IEC 62684-2011-01- Consumption in passive mode < 0.1 W- 2P+E tap-off connection via 2.5 mm² screw terminals- Supplied without cordDouble USB sockets - 5 V - 2400 mA- (1500 mA until 1st July 2016)- For fast charging telephones, smartphones, MP3/MP4 players and tablet PC- 2 modules - Magnesium- Can be installed in receptacles for floor sockets

Technical characteristics

Model	Other	**degree of impact strength (IK)**	IK04
Number of ports USB-A	2	**Antimicrobial treatment**	No
Number of ports USB-C	0	**Built-in depth**	33.5 mm
Operating voltage (Min-Max)	100-240 V	**Operating / setting temperature (Min-Max)**	5-40 °C
Frequency (Min-Max)	50-60 Hz	**Storage temperature (Min-Max)**	-20-70 °C
Max. output current	3000 mA	**Voltage type**	AC
Connection type	Screwed terminal	**Power Delivery**	No
Mounting method	Module frame	**USB Output Power**	15
Colour	Aluminium	**Mandatory neutral**	Yes
RAL-number	7040	**Terminal marking indication**	Yes
Device width	45 mm	**Stress test conformity (1000V)**	No
Device height	45 mm	**Halogen free**	Yes

Device depth	42 mm
Min. depth of built-in installation box	40 mm
Suitable for degree of protection (IP)	IP40

Terminals capacity (Min-Max)	1.5-2.5 mm^2
Cable section (Min-Max)	1.5-2.5 mm^2

Documentation

TECHNICAL DOCUMENTATION

F01498FR-07.pdf | PDF (0.1Mo)

F01498EN-07.pdf | PDF (0.1Mo)