Product sheet



PROGRAMME MOSAIC LEGRAND

TV socket Mosaic - single type "F" - 1 module - white

REF. 078790 | EAN. 3414970997975

> Visit e-catalogue

Product charateristics

- Mosaic™ Programm e mechanisms - television sockets - For DVBT, Cablecast and satellite installation - UHD TV compatible - Class A shielded star sockets LTE Ready (4G protected) Recomm ended coaxial cable : 17 VATC - Star cabling (1 socket = 1 cable to antenna, splitter or multiswitch) Visual checking of the connection - Meet EN 50083 - 4 and EN 50083 - 2 European directive - TV : male connector (Ø9.5 mm) - 5 - 68 / 120 - 862 MHz - R : female connector (Ø9.5 mm) - 87.5 - 108 MHz - SAT : "F type" connector - 950 - 2400 MHz
- Single TV star sockets - Low attenuation : 1 dB TV "F - type" - White - 1 module

Technical characteristics

Model	End socket
Type of socket outlet	TV
DAB+	No
Mounting method	Module frame
Number of modules (module system)	1
Assembly arrangement	Modular device for domestic switching devices
Tap loss at 860 MHz	1 dB
Tap loss at 2150 MHz	1.5 dB
Number of outlets	1
Suitable for cable modem	No
Suitable for remote power supply	Yes
Type of fastening	Snap mounting (engagement)
Colour	White
RAL-number (similar)	9003

Surface protection	Untreated
Surface finishing	Glossy
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Degree of protection (IP)	IP21
degree of impact strength (IK)	IK03
Device width	22.5 mm
Device height	45 mm
Device depth	35.5 mm
Min. depth of built-in installation box	23.5 mm
Operating / setting temperature (Min-Max)	-5-35 °C
Storage temperature (Min-Max)	-10-70 °C

Documentation

TECHNICAL DOCUMENTATION

S000090598EN-02.pdf | PDF (0.33Mo)

LE08364AA.pdf | PDF (1.51Mo)

CAD & Design specs / BIM

BIM-LEGRAND-MOSAIC-2025-12-ENGLISH.rvt | RVT (127.11Mo)

BIM-LEGRAND-MOSAIC-2025-ENGLISH.rvt | RVT (125.73Mo)