Product sheet



LEGRAND

Flush-mounted socket outlet - SKT 13A 2G DP White - Screwed terminal - Enhanced contact protection - IP40 protection

REF. 678142 | EAN. 3245066781426

Introducing the Legrand SKT 13A 2G DP White socket Outlet. Flush-mounted, BS compliant, IP40 rated, supports flexible/rigid cables, with contact protection and on/off switch.

> Visit e-catalogue

Description

Introducing the Legrand SKT 13A 2G DP White socket Outlet. Flush-mounted, BS compliant, IP40 rated, supports flexible/rigid cables, with contact protection and on/off switch.

Technical characteristics

Model	British Standard
Concurrently switching neutral conductor	Yes
Protective contact	Flat
Number of active contacts (round)	0
Number of active contacts (flat)	4
Number of active contacts (square)	0
Assembly arrangement	Modular device for domestic switching devices
With complemantary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of socket outlets	2
Number of modules (module system)	4
Number of socket outlets switchable	2
Number of phases	1
Imprint/indication	None
Connection type	Screwed terminal

Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	Yes
Colour of switch operator	White
Rotated central insert	No
Nominal current	13 A
Nominal voltage	250 V
Frequency (Min-Max)	50-60 Hz
Suitable for degree of protection (IP)	IP40
degree of impact strength (IK)	IK04
Device width	144 mm
Device height	79 mm

With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No
Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Overvoltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	None
Mounting method	Flush-mounted
Type of fastening	Mounting with screw

Device depth	31 mm
Compatible with Apple HomeKit	No
Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	23.9 mm
Operating / setting temperature (Min-Max)	-5-35 °C
Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Flexible or rigid
Cable section (Min-Max)	4-4 mm^2
Cable support	Other
Connected object	No

Documentation

TECHNICAL DOCUMENTATION

F01386EN-00.pdf | PDF (0.86Mo)

Agreements & Certificates

OC / CB-FR_706622/M1 | (0.32Mo)

CAD & Design specs / BIM

BIM-LEGRAND-MOSAIC-2025-12-ENGLISH.rvt | RVT (127.11Mo)

BIM-LEGRAND-MOSAIC-2025-ENGLISH.rvt | RVT (125.73Mo)