

Synergy™ fused connection units, shaver sockets, cooker control units, cable outlets and blanking plates - Flat plate



Terminal screws captive and backed off ready for cabling - large angled terminal entries
 Compact mechanism for maximised wiring space
 Supplied with transparent protection cover and 4 fixing screws (2 long and 2 short screws)

Pack	Cat.Nos	Fused connection units unswitched 13 A - 250 V~
1	7 342 32	Conform to BS 1363: Part. 4 Front cable outlet with cord grip Fuses supplied Locked captive fuse carrier (padlockable) For flush-mounting, back box to be min. 35 mm deep Supplied with 2 gang frame Cat.No 7 341 99 (3 mm thick) in case of extra wiring space needed
1	7 346 32	Unswitched - with cord outlet Nominal plate dimensions: 86 x 86 mm ● Antique Brass ● Brushed stainless steel
1	7 342 34	Fused connection units switched 13 A - 250 V~ Conform to BS 1363: Part. 4 Front cable outlet with cord grip Fuses supplied Locked captive fuse carrier (padlockable) For flush-mounting, back box to be min. 35 mm deep Supplied with 2 gang frame Cat.No 7 341 99 (3 mm thick) in case of extra wiring space needed
1	7 346 34	DP switched - without cord outlet Nominal plate dimensions: 86 x 86 mm ● Antique Brass ● Brushed stainless steel
1	7 342 37	DP switched - with red LED power indicator + cord outlet Nominal plate dimensions: 86 x 86 mm ● Antique Brass ● Brushed stainless steel
1	7 346 37	
1	7 342 90	Shaver sockets Conform to BS EN 61558-2-5 suitable for use with European, British, American and Australian 2 pin plugs Rating: 20 VA IP 24 Screwless live and neutral terminals For flush-mounting, back box to be min. 45 mm deep Supplied with 2 gang frame Cat.No 7 341 99 (3 mm thick) in case of extra wiring space needed
1	7 346 90	240 V / 120 V - 50/60 Hz Nominal plate dimensions: 146 x 86 mm ● Antique Brass ● Brushed stainless steel

Pack	Cat.Nos	Cooker control units - 250 V~
1	7 342 29	Conform to BS 4177: 1992 For flush-mounting, back box to be min 47 mm deep
1	7 346 29	45 A DP switch + 13 A DP switched socket outlet Nominal plate dimensions: 86 x 146 mm ● Antique Brass ● Brushed stainless steel
1	7 342 19	Cable outlets Conform to BS 5733 Fitted with clamp and outlet membrane With terminal block
1	7 346 19	20 A - 250 V~ Nominal plate dimensions: 86 x 86 mm ● Antique Brass ● Brushed stainless steel
1	7 342 26	45 A - 250 V~ Nominal plate dimensions: 86 x 86 mm ● Antique Brass ● Brushed stainless steel
1	7 346 26	
1	7 342 95	Blanking plates 1 gang Nominal plate dimensions: 86 x 86 mm ● Antique Brass ● Brushed stainless steel
1	7 346 95	
1	7 342 96	2 gang Nominal plate dimensions: 86 x 146 mm ● Antique Brass ● Brushed stainless steel
1	7 346 96	