

# Product datasheet

Specifications

## Category 5e UTP 24-port Patch Panel, loaded



DCEPP24UKY1U

⚠ Discontinued on: 13 June 2023

⚠ Discontinued

### Main

Range	Digilink
Product or component type	Patch panel
Provided equipment	With RJ45 connectors
Communication network category	5e
Cable shielding type	UTP
Number of port	24

### Complementary

Connector type	RJ45
Minimum number of matings	750 cycles
[In] rated current	1.5 A
Insulation resistance	>= 500 mOhm at 500 V DC
Contact resistance	20 mOhm
Material	Panel: steel powder coated
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Width	482.6 mm
Height	44.2 mm
Number of rack unit	1U

### Environment

Environmental characteristic	Flame retardant
Product certifications	UL/ETL verified
Standards	ISO/IEC 11801 class D EIA/TIA TSB 40 A ANSI/TIA-568-C.2

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	6 cm
Package 1 Width	8.5 cm
Package 1 Length	49.14 cm
Package 1 Weight	1.05 kg
Unit Type of Package 2	S04
Number of Units in Package 2	13
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	14.09 kg
Unit Type of Package 3	P12
Number of Units in Package 3	104
Package 3 Height	80 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	119.12 kg

Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)