



Wattstopper's CI-355 passive infrared (PIR) occupancy sensor automatically turns lighting on and off based on occupancy. The sensor mounts on the ceiling with a flat, low-profile appearance and provides 360 degrees of coverage.

## Features & Benefits

Detection Signature Processing eliminates false triggers and provides immunity to RFI and EMI	Walk-through mode turns lights off 3 minutes after the area is initially occupied – ideal for brief visits such as mail delivery
Built-in light level sensor featuring simple, one-step setup	Zero-crossing for long relay life
LED indicates occupancy detection	DIP switch simplifies sensor adjustments
Clip mounting system makes ceiling tile installation simple 360 degree coverage, up to 1200 sqft	

## Specifications

### General Info

Product Line	Wattstopper	Color	White
Finish	Glossy	UPC Number	754182914333
Country Of Origin	China	Material	ABS
Product Series	CI-355	Features	Adjustable Time Delay, Indicator Lights, Light Level Sensor, Sensitivity Adjustment
Installation Location	Ceiling	Included	Mounting Screws, Sensor Mask
Application Sector	Commercial	Standard	UL, cUL
Warranty Type	5-Year	Type	Sensor

### Dimensions

Product Width US	4.5 in	Product Weight US	0.3 lb
------------------	--------	-------------------	--------

Product Volume US	59.0 cu in	Product Depth US	2.1 in
Product Height US	4.5 in		
<b>Additional Information</b>			
RoHS Compliant	Yes	Product Environmental Profile	Yes
<b>Technical Information</b>			
Operating Temperature Min	32 °F	Timer Type	DIP Switch
Load Rating	1200 W @ 230-347 VAC, 800 W @ 120 VAC	Has Battery	No
Sensor Coverage Pattern	360 °	Sensor Type	Occupancy
Operating Temperature Max	131 °F	Sensor Mounting Height	8-12 ft
Light Level Adjustment	10-300 fc	Number of Buttons	0
Lens Type	Extended Range	Number of Rockers	0
Sensor Technology	Passive Infrared (PIR)	Timer Duration	30 Seconds, 5-30 Minutes
Indicator	PIR Detection LED	Input Voltage	120/230/277/347 VAC
Line Frequency	50 Hz, 60 Hz	Indoor/Outdoor	Indoor
Sensor Coverage	1200 sq ft	Sensitivity Adjustment	PIR (Min/Max)
Mounting Type	2-1/4 in Deep J-Box, Surface	On Function	Auto On
Operating Temperature	0°-55°C, 32°-131°F	Operating Humidity	5-95% RH (Non-Condensing)
Sensing Range	44 ft diameter	Location Rating	Dry
Wire Connection Type	Flying Leads	Engraving Type	Blank
Storage Temperature	23° - 176° F, -5° - 80° C		