

Product sheet



SYNERGY™ LEGRAND

Synergy™ Sleek - 2 gang 2-way switch - 10AX - Brushed Stainless Steel

REF. 832002 | EAN. 3414970660428

> [Visit e-catalogue](#)

Product characteristics

- 10AX, 250V~
- Screw type terminals, marked for easy identification
- Large angled easy - to - access cable entries and captive screws
- Screwless cover plate is square 86x86 mm, product thickness is 4mm (once is installed onto the wall).
- Complete product, cover plates are clipped onto the mechanism itself.

Recommendation / Restriction

- Recommended inside use only

Installation

- Strip length indicator avoids waste of wires. Terminal screws backed off ready to cabling

Usage

- Can be used as a simple switch but can also be associated with another two-way switch, thus allowing to turn the light on and off from two different control points.

Advantages

- Plate and rockers in same metal: austenitic stainless steel Non magnetic Grade 304L
- Made in UK
- Delivered with screws for flush & surface boxes in both plastic and metal boxes

Technical characteristics

Wiring system	Two-way switch	Nominal voltage	250 V
Method of operation	Rocker/button	Rated current	10 A
Assembly arrangement	Basic element with full cover plate	Switching current for fluorescent lamps	10 AX
Push button switch	No	Monitoring contact	No
Number of rockers	2	Connection type	Screwed terminal
Mounting method	Flush-mounted	Heating switch	No
Type of fastening	Screw mounting	Washing machine switch	No
		Device width	86 mm

With mounting plate	Yes	Device height	86 mm
Material	Metal	Device depth	26 mm
Material quality	Stainless steel	Built-in depth	14 mm
Halogen free	Yes	Min. depth of built-in installation box	30 mm
Antimicrobial treatment	No	Compatible with Apple HomeKit	No
Surface protection	Metallic	Compatible with Google Assistant	No
Surface finishing	Glossy	Compatible with Amazon Alexa	No
Colour	Stainless steel	IFTTT support available	No
Colour of switch operator	Stainless steel	Operating / setting temperature	-5-40 °C
Label space/information surface	No	Storage temperature	-5-40 °C
Lighting	No	Voltage type	AC
Function lighting	Other	Frequency	50-60 Hz
Type of lighting	Other	Cable section	4-4 mm ²
Suitable for degree of protection (IP)	IP2X		
degree of impact strength (IK)	IK01		

Documentation

TECHNICAL DOCUMENTATION

 F02254EN-01.pdf | PDF (0.68Mo)

Agreements & Certificates

 OC / CB-FR_708093 | (0.72Mo)

 ASTA-781 | (0.4Mo)

CATALOGUE PAGE & OTHERS

 ex223001_0727.pdf | PDF (0.08Mo)