

Synergy® Authentic

fan switch and double pole switches



8334 09



8330 10



8332 16



8334 12



8330 22



8332 23



8334 21

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos.	3 pole fan switch 10 A - 250 V~
1	8330 09	Conform to BS EN 60669-1 : 2000
1	8332 09	With integrated padlockable safety block in OFF position
1	8334 09	Flush mounting back box : min. 25 mm deep
		Nominal plate dimensions : 86 x 86 mm
		● Brushed stainless steel
		● Polished stainless steel
		● Gold
		Double pole switches 20 A - 250 V~
		Conform to BS EN 60669-1
		Flush mounting back box : min. 25 mm deep
		Use cord outlet accessory Cat.No 7300 53 p.38
		for external cord outlet
		Nominal plate dimensions : 86 x 86 mm
		DP switch
1	8330 10	● Brushed stainless steel
1	8332 10	● Polished stainless steel
1	8334 10	● Gold
		DP switch + cord outlet + blue LED power indicator
1	8330 16	● Brushed stainless steel
1	8332 16	● Polished stainless steel
1	8334 16	● Gold
		DP switch + blue LED power indicator
1	8330 12	● Brushed stainless steel
1	8332 12	● Polished stainless steel
1	8334 12	● Gold

Pack	Cat.Nos.	Double pole switches 45 A - 250 V~
		Conform to BS EN 60669-1
		Flush mounting back box : min. 45 mm deep
		1 gang switch
		Nominal plate dimensions : 86 x 86 mm
1	8330 22	● Brushed stainless steel
1	8332 22	● Polished stainless steel
1	8334 22	● Gold
		1 gang switch + blue LED power indicator
		Nominal plate dimensions : 86 x 86 mm
1	8330 23	● Brushed stainless steel
1	8332 23	● Polished stainless steel
1	8334 23	● Gold
		1 gang switch + blue LED power indicator large plate
		Nominal plate dimensions : 146 x 86 mm
1	8330 21	● Brushed stainless steel
1	8332 21	● Polished stainless steel
1	8334 21	● Gold

Synergy® Authentic

cooker control units and fused connection units



Synergy® Authentic

shaver sockets, cable outlets, blanking plates and cord outlets



8332 29



8334 37

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries. Compact mechanism for maximum wiring space

Pack	Cat.Nos.	Cooker control units - 250 V~
		Conform to BS 4177 : 1992 Flush mounting back box : min. 47 mm deep Nominal plate dimensions : 86 x 146 mm
		45 A DP switch + 13 A DP switched socket outlet with blue LED power indicator
1	8330 29	● Brushed stainless steel
1	8332 29	● Polished stainless steel
1	8334 29	● Gold
		Fused connection units 13 A - 250 V~
		Conform to BS 1363 : Part. 4 Front cable outlet with cord grip Fuse supplied Locked captive fuse carrier (padlockable) Flush mounting back box : min. 25 mm deep
		Unswitched with cord outlet
		Nominal plate dimensions : 86 x 86 mm
1	8330 32	● Brushed stainless steel
1	8332 32	● Polished stainless steel
1	8334 32	● Gold
		Unswitched without cord outlet
		Nominal plate dimensions : 86 x 86 mm
1	8330 30	● Brushed stainless steel
1	8332 30	● Polished stainless steel
1	8334 30	● Glossy gold
		Unswitched with blue LED power indicator
		Nominal plate dimensions : 86 x 86 mm
1	8330 31	● Brushed stainless steel
1	8332 31	● Polished stainless steel
1	8334 31	● Gold
		Unswitched with blue LED power indicator + cord outlet
		Nominal plate dimensions : 86 x 86 mm
1	8330 33	● Brushed stainless steel
1	8332 33	● Polished stainless steel
1	8334 33	● Gold
		DP switched without cord outlet
		Nominal plate dimensions : 86 x 146 mm
1	8330 34	● Brushed stainless steel
1	8332 34	● Polished stainless steel
1	8334 34	● Gold
		DP switched with blue LED power indicator
		Nominal plate dimensions : 86 x 146 mm
1	8330 35	● Brushed stainless steel
1	8332 35	● Polished stainless steel
1	8334 35	● Gold
		DP switched with blue LED power indicator + cord outlet
		Nominal plate dimensions : 86 x 146 mm
1	8330 37	● Brushed stainless steel
1	8332 37	● Polished stainless steel
1	8334 37	● Gold



8332 90



8330 19



8334 95

Slim front plates:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries. Compact mechanism for maximum wiring space

Pack	Cat.Nos.	Shaver sockets
		Conform to BS EN 61558-2-5 Suitable for use with European, British and Australian 2 pin plugs Rating : 20 VA IP 24 Screwless live and neutral terminals Flush mounting back box : min. 45 mm deep Nominal plate dimensions : 146 x 86 mm
		230/120 V~ - 50/60 Hz
1	8330 90	● Brushed stainless steel
1	8332 90	● Polished stainless steel
1	8334 90	● Gold
		Cable outlets
		Conform to BS 5733 Fitted clamp and outlet membrane With terminal block Nominal plate dimensions : 86 x 86 mm
		20 A - 250 V~
1	8330 19	● Brushed stainless steel
1	8332 19	● Polished stainless steel
1	8334 19	● Gold
		45 A - 250 V~
1	8330 26	● Brushed stainless steel
1	8332 26	● Polished stainless steel
1	8334 26	● Gold
		Blanking plates
		1 gang
		Nominal plate dimensions : 86 x 86 mm
1	8330 95	● Brushed stainless steel
1	8332 95	● Polished stainless steel
1	8334 95	● Gold
		2 gang
		Nominal plate dimensions : 86 x 146 mm
1	8330 96	● Brushed stainless steel
1	8332 96	● Polished stainless steel
1	8334 96	● Gold
		Cord outlets
		1 gang
		Nominal plate dimensions : 86 x 86 mm
1	8330 52	● Brushed stainless steel
1	8332 52	● Polished stainless steel
1	8334 52	● Gold