



Wattstopper
Dual Tech Occupancy Sensor 100 -347 VAC, center mount 360°
Part No. DT-355



Wattstopper's low profile DT-355 dual technology occupancy sensor combines the benefits of passive infrared (PIR) and ultrasonic technologies. The sensor mounts on the ceiling with a flat, unobtrusive appearance and provides 360 degrees of coverage.

Features & Benefits

Architecturally appealing low profile appearance

Ultrasonic diffusers give more comprehensive coverage

Operates at 120, 230 (single phase), 277 or 347 VAC, 50/60 Hz

Terminal wiring for quick and easy installation

Walk-through mode increases savings potential

Specifications

General Info

Product Line	Wattstopper	Color	White
Finish	Glossy	UPC Number	754182913848
Country Of Origin	China	Material	ABS
Product Series	DT-355	Features	Adjustable Time Delay, Indicator Lights, Light Level Sensor, Sensitivity Adjustment, Test Mode, Walkthrough Mode
Switch Type	Motion Sensor	Installation Location	Ceiling
Included	Mounting Screws, Sensor Mask	Application Sector	Commercial
Standard	UL, cUL	Warranty Type	5-Year
Type	Sensor		

Dimensions

Product Width US	4.5 in	Product Weight US	0.2 lb
Product Volume US	44.4 cu in	Product Depth US	1.5 in
Product Height US	4.5 in		

Additional Information

RoHS Compliant	Yes	Product Environmental Profile	Yes
----------------	-----	-------------------------------	-----

Technical Information

Operating Temperature Min	32 °F	Timer Type	DIP Switch
Load Rating	1200 W @ 230-347 VAC, 800 W @ 120 VAC	Compatibility	BZ Power Packs, Wattstopper PLUS Sensor Interface Module
Ultrasonic Frequency	40 kHz	Has Battery	No
Sensor Coverage Pattern	360 °	Sensor Type	Occupancy
Operating Temperature Max	131 °F	Sensor Mounting Height	8-12 ft
Light Level Adjustment	10-300 fc	Number of Buttons	0
Number of Rockers	0	Sensor Technology	Dual Technology, Passive Infrared (PIR), Ultrasonic
Timer Duration	30 Seconds, 5-30 Minutes	Indicator	PIR Detection LED, Ultrasonic Detection LED
Input Voltage	120/230/277/347 VAC	Line Frequency	50 Hz, 60 Hz
Indoor/Outdoor	Indoor	Sensor Coverage	1000 sq ft
Sensitivity Adjustment	PIR (Min/Max), Ultrasonic (Min/Max)	Mounting Type	2-1/4 in Deep J-Box, 4 in Octagonal J-Box, Surface

On Function	Auto On	Operating Temperature	0°-55°C, 32°-131°F
Operating Humidity	5-95% RH (Non-Condensing)	Sensing Range	36 ft
Location Rating	Dry	Wire Connection Type	Flying Leads
Engraving Type	Blank	Storage Temperature	23° - 176° F, -5° - 80° C