



2814 72



2812 84



2814 90

Front plates material : Polycarbonate. Supplied with 2 screws M 3.5 for BS boxes. Dim.: 86.5 x 86.5 x 10.5 mm

Pack	Cat.Nos	Double pole switches (continued)
	White	45 A - 250 V Conform to BS EN 60669 - 1
10	2810 71	1 gang - 1 way, with red indicator
10	2810 72	1 gang - 1 way, with red indicator with cooker marking
10	2810 73	2 gang - 1 way vertical switch, with red indicator
	Silver Champagne	
5	2812 71 2814 71	1 gang - 1 way, with red indicator
5	2812 72 2814 72	1 gang - 1 way, with red indicator with cooker marking
5	2812 73 2814 73	2 gang - 1 way vertical switch, with red indicator
	White	Cooker control unit Conform to BS 4177
10	2810 75	45 A DP switch + 13 A switched socket outlet with red indicator
	Silver Champagne	
5	2812 75 2814 75	45 A DP switch + 13 A switched socket outlet with red indicator

Pack	Cat.Nos	Dimmers
1	White	
1	2810 80	60-500 W rotary control dimmer for incandescent and halogen lamps 230 V - 60-300 VA ELV halogen lamps with ferromagnetic transformer and compensator Cat.No 401 39 (p. 458)
1	2810 84	500 W rotary control dimmer + 2 way switch - for incandescent and halogen lamps 230 V
	Silver Champagne	
1	2812 80 2814 80	60-500 W rotary control dimmer for incandescent and halogen lamps 230 V - 60-300 VA ELV halogen lamps with ferromagnetic transformer and compensator Cat.No 401 39 (p. 458)
1	2812 84 2814 84	500 W rotary control dimmer + 2 way switch - for incandescent and halogen lamps 230 V

Pack	Cat.Nos	Fan speed control
	White	
1	2810 82	5 speed fan control 100 W for fan with overall diameter 48"
	Silver Champagne	
1	2812 82 2814 82	5 speed fan control 100 W for fan with overall diameter 48"

Pack	Cat.Nos	Automatic switch
	White	Automatic switch with infrared movement detector Horizontal detection angle 180° Luminosity threshold: 43 to 1614 lux Detection range: max. 12 m Compatible load: 25 - 200 W for incandescent and halogen lamps 230 V Temporization: 20 s - 15 min
1	2810 90	Automatic switch
	Silver Champagne	
1	2812 90 2814 90	Automatic switch

Pack	Cat.Nos	Time delay switch
	White	Adjustable time from 5 min to 12 h Maximum load : 500 W incandescent and halogen lamps 230 V - 250 W fluorescent lamps without capacitor
1	2810 91	Time delay switch
	Silver Champagne	
1	2812 91 2814 91	Time delay switch

Pack	Cat.Nos	Programmable switch
	White	Power supply: 230 V - 50/60 Hz Maximum load: 2300 W Weekly programme Capacity: max. 28 programmes Output: 1 changeover contact
1	2810 92	Programmable switch
	Silver Champagne	
1	2812 92 2814 92	Programmable switch