

Arteor™

audio and video sockets



Support frame and plate selection charts **p. 86-93**

Mechanisms supplied with rocker plates, to be equipped with support frames (p. 75) and plates (p. 76-85)

Pack	Cat.Nos	
		HDMI type A sockets Used to transmit high-definition digital audio/video streams between a source (Blu-ray player, computer) and a compatible receiver (TV, videoprojector...) Preterminated sockets HDMI 1.4 - 1 module Equipped with cord, length 15 cm <ul style="list-style-type: none"> ○ White ● Magnesium Preterminated sockets HDMI 1.4 - 2 modules Equipped with cord, length 15 cm <ul style="list-style-type: none"> ○ White ● Magnesium Screw-type sockets HDMI 1.3 - 2 modules <ul style="list-style-type: none"> ○ White ● Magnesium
1	Square version 5 720 96	
1	Round version -	
1	5 725 96	
1	-	5 724 76
1	-	5 735 96
1	5 722 81 ¹	5 722 85
1	5 727 81 ¹	5 727 85
		HD15 + 3.5 mm Jack amplifier Used to connect audio/video terminals more than 20 m apart up to 100 m The video link is via an HD15 connector (resolution up to UXGA) The stereo audio link is via a 3.5 mm Jack The kit includes: - 1 4-module transmitter equipped with an HD15 connector and a 3.5 mm Jack - 1 4-module receiver equipped with an HD15 connector and a 3.5 mm Jack - 1 4-module power supply to be connected on the mains then linked to the receiver or transmitter The link between the transmitter and receiver is via a twisted pair cable <ul style="list-style-type: none"> ○ White
1	Square version 5 723 70	
		HDMI extender Extends HDMI audio/video signals up to 57 m up to a 4 K resolution using HD BaseT Lite technology Kit includes both transmitter and receiver with link via a network cord RJ 45/RJ 45 (p. 701-707) Supports 3D video, HDCP, 4K resolution, EDID passthrough and IR control, HD BaseT certified
1	N 0 517 38	
		Display port sockets Used to transmit high-definition digital audio/video streams between a source (laptop, computer, etc) and a compatible receiver (TV, videoprojector...) Preterminated socket - 1 module Equipped with cord, length 15 cm <ul style="list-style-type: none"> ○ White ● Magnesium Preterminated socket - 2 modules Equipped with cord, length 15 cm <ul style="list-style-type: none"> ○ White ● Magnesium
1	Square version 5 720 90	
1	5 725 90	
1	Round version 5 724 70	
1	5 735 90	
		HD15 sockets Used to transmit analog video streams (VGA, XGA, UXGA depending on graphic card) between a source (computer) and a compatible receiver (LCD, video projector, TV, etc...) Preterminated sockets - 1 module Equipped with cord, length 15 cm <ul style="list-style-type: none"> ○ White ● Magnesium Preterminated HD15 + 3.5 mm Jack sockets - 2 modules Equipped with cord, length 15 cm <ul style="list-style-type: none"> ○ White ● Magnesium Screw-type female HD15 sockets 2 modules <ul style="list-style-type: none"> ○ White ● Magnesium Screw-type female HD15 + 3.5 mm Jack sockets - 2 modules <ul style="list-style-type: none"> ○ White ● Magnesium Solder-type female HD15 sockets 1 module 15 pin <ul style="list-style-type: none"> ○ White ● Magnesium
1	Square version 5 720 97	Round version -
1	5 725 97	-
1	-	5 724 78
1	-	5 733 78
1	5 722 82 ¹	5 722 89
1	5 727 82 ¹	5 727 89
1	5 722 88	-
1	5 727 88	-
1	5 722 79	-
1	5 727 79	-

Floor sockets see **p. 67**



1: Can be installed in receptacles for floor sockets p. 67