



Wattstopper's low-profile UT-355 Ultrasonic Line Voltage Ceiling Sensor automatically turns lighting on and off based on occupancy. The sensor mounts on the ceiling with a flat, unobtrusive appearance and provides 360° coverage.

## Features & Benefits

Architecturally appealing low-profile appearance	Utilizes advanced, omni-directional, ultrasonic technology
Ultrasonic diffusers provide more comprehensive coverage	Operates at 120, 230 (single phase), 277 or 347 VAC, 50/60 Hz
Terminal wiring for quick and easy installation	Walk-through mode increases savings potential

## Specifications

### General Info

Product Line	Wattstopper	Color	White
Finish	Glossy	UPC Number	754182915224
Country Of Origin	China	Material	ABS
Product Series	UT-355	Features	Adjustable Time Delay, Indicator Lights, Light Level Sensor, Sensitivity Adjustment
Installation Location	Ceiling	Included	Mounting Screws
Application Sector	Commercial	Standard	UL, cUL, PEP
Warranty Type	5-Year	Type	Sensor

## Dimensions

Product Width US	4.5 in	Product Weight US	0.337 lb
Product Volume US	69.6 cu in	Product Depth US	1.9 in
Product Height US	4.5 in		

## Additional Information

RoHS Compliant	Yes	Product Environmental Profile	Yes
----------------	-----	-------------------------------	-----

## Technical Information

Operating Temperature Min	32 °F	Timer Type	DIP Switch
Load Rating	1200 W @ 230 VAC, 1200 W @ 277 VAC, 1500 W @ 347 VAC, 800 W @ 120 VAC	Ultrasonic Frequency	40 kHz
Has Battery	No	Sensor Coverage Pattern	360 °
Sensor Type	Occupancy	Operating Temperature Max	131 °F
Sensor Mounting Height	8-10 ft	Light Level Adjustment	10-300 fc
Number of Buttons	0	Number of Rockers	0
Sensor Technology	Ultrasonic	Timer Duration	30 Seconds, 5-30 Minutes
Indicator	Ultrasonic Detection LED	Input Voltage	120/230/277/347 VAC
Line Frequency	60 Hz	Indoor/Outdoor	Indoor
Sensor Coverage	2000 sq ft	Sensitivity Adjustment	Ultrasonic (0-100%)
Mounting Type	2-1/4 in Deep J-Box, Surface	On Function	Auto On
Operating Temperature	0°-55°C, 32°-131°F	Operating Humidity	5-95% RH (Non-Condensing)
Sensing Range	10 x 60 ft, 40 x 40 ft	Location Rating	Dry

---

Wire Connection Type	Screw Terminals	Engraving Type	Blank
----------------------	-----------------	----------------	-------

---

Storage Temperature	23° - 176° F, -5° - 80° C
---------------------	---------------------------

---