

# Product sheet



## SYNERGY™ LEGRAND

Synergy™ Sleek - 1 gang switched single pole BS socket outlet 13A - Glossy Gold

REF. 832466 | EAN. 3414970663368

> [Visit e-catalogue](#)

## Product characteristics

- 2p+E British Standard, 13A, 250V
- Conform to BS1363 - 2, ASTA Licence
- Screw type terminals for a secured & enhanced contacts
- Screwless cover plate is square 86x86 mm, product thickness is 4mm (once is installed onto the wall).
- Complete product, cover plates are clipped onto the mechanism itself.

## Recommendation / Restriction

- Recommended inside use only

## The product's benefits

### Installation

- Strip length indicator avoids waste of wires. Captive terminal screws backed off ready to cabling

### Usage

- Fitted with safety shutters to maximise child protection

### Advantages

- Plate and switch rocker are made in the same Stainless Steel - Grade 430, with a chromium plating which bring a better rusting resistance and a nicer finish
- Made in UK
- Delivered with screws for flush & surface boxes in both plastic and metal boxes

## Technical characteristics

Model	British Standard	Material	Metal
Concurrently switching neutral conductor	No	Material quality	Stainless steel
Protective contact	Flat	Halogen free	Yes
Number of active contacts (round)	0	Surface protection	Metallic
Number of active contacts (flat)	2	Surface finishing	Glossy
Number of active contacts (square)	0	Antimicrobial treatment	No

Assembly arrangement	Basic element with full cover plate	With loop through function	Yes
With complementary luminous signal	No	With on/off switch	Yes
Number of ports USB-A	0	Rotated central insert	No
Number of ports USB-C	0	Nominal current	13 A
Number of socket outlets	1	Nominal voltage	250 V
Socket outlets phase-separated	No	Frequency (Min-Max)	50-60 Hz
Number of modules (module system)	2	Suitable for degree of protection (IP)	IP2X
Number of socket outlets switchable	1	degree of impact strength (IK)	IK01
Number of phases	1	Device width	86 mm
Imprint/indication	Other	Device height	86 mm
Connection type	Screwed terminal	Device depth	29 mm
With hinged lid	No	Compatible with Apple HomeKit	No
With enhanced contact protection	No	Compatible with Amazon Alexa	No
Label space/information surface	No	Compatible with Google Assistant	No
Colour	Gold	IFTTT support available	No
Metallic colour	Yes	With Wi-Fi signal repeater	No
Transparent	No	With built-in bluetooth speaker	No
Lockable	No	For heavy conditions according to VDE	No
Eject-mechanism	No	Built-in depth	25 mm
Insulated mounting	No	Operating / setting temperature (Min-Max)	-5-40 °C
With function lighting	No	Storage temperature (Min-Max)	-5-40 °C
With orientation lighting	No	Voltage type	AC
Overvoltage protection	No	Power Delivery	No
Fault current protection	No	Cable nature for connection	Flexible or rigid
With miniature fuse	No	Cable section (Min-Max)	6-6 mm <sup>2</sup>
Special power supply	None	Cable support	Other
Mounting method	Flush-mounted	Connected object	No
Type of fastening	Mounting with screw		

## Documentation

### TECHNICAL DOCUMENTATION

 F02263EN-00.pdf | PDF (0.7Mo)

### Agreements & Certificates

### CATALOGUE PAGE & OTHERS

 ex223001\_0728.pdf | PDF (0.08Mo)

█ G-MARK-0003-2358 R 1 | (0.51Mo)

█ ASTA-780 | (0.28Mo)