


Product sheet



ARTEOR LEGRAND

Arteor 2 Way Double Pole Lighting Control Master Switch Square 20AX - 2 Module - Magnesium

REF. 573784 | EAN. 3245065737844

Arteor hotel equipment - square version - Mechanisms supplied with rocker plates , to be equipped with support frames and plates

> [Visit e-catalogue](#)

Description

Arteor hotel equipment - square version - Mechanisms supplied with rocker plates , to be equipped with support frames and plates

Product characteristics

- Arteor™ hotel equipment - square version- Mechanisms supplied with rocker plates, to be equipped with support frames and plates
- Lighting controlMaster switch - 2 modules- 2-way double pole- 20 AX - 250 V~ for general control: all ON / all OFF - Magnesium

Technical characteristics

Wiring system	Two-way switch
Method of operation	Rocker/button
Assembly arrangement	Modular device for domestic switching devices
Number of modules (module system)	2
Push button switch	No
Number of rockers	1
Mounting method	Module frame
Type of fastening	Engage (snap)
With mounting plate	No
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No

Function lighting	Other
Type of lighting	Other
Suitable for degree of protection (IP)	IP40
degree of impact strength (IK)	IK04
Nominal voltage	250 V
Rated current	20 A
Switching current for fluorescent lamps	20 AX
Monitoring contact	No
Connection type	Screwed terminal
Device width	45 mm
Device height	45 mm
Device depth	42.2 mm
Built-in depth	28.5 mm
Min. depth of built-in installation box	30 mm

Surface protection	Lacquered
Surface finishing	Matt
Colour	Grey
Colour of switch operator	Grey
Label space/information surface	No
Lighting	No

Operating / setting temperature (Min-Max)	-5-50 °C
Storage temperature (Min-Max)	-10-70 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz
Cable section (Min-Max)	4-4 mm²

Documentation

Agreements & Certificates



OC / CB-FR_705038/M1 | (2.34Mo)