

Product sheet

**SYNERGY™ LEGRAND****Synergy™ - Switch Grid module - intermediate - 20 AX
- 250 V~ - White**

REF. 735418 | EAN. 3245067354186

[> Visit e-catalogue](#)

Product characteristics

- Single pole switches 20 AX - 250 V~ - Conform to BS EN 60669 - 1 - White - Intermediate

Technical characteristics

Wiring system	Intermediate switch
Method of operation	Rocker/button
Assembly arrangement	Basic element with central cover plate
Push button switch	No
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Other
With mounting plate	No
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Glossy
Colour	White
RAL-number (similar)	9003
Colour of switch operator	White

Function lighting	Other
Type of lighting	Other
Suitable for degree of protection (IP)	IP2X
degree of impact strength (IK)	IK01
Nominal voltage	250 V
Rated current	20 A
Switching current for fluorescent lamps	20 AX
Monitoring contact	No
Connection type	Screwed terminal
Device width	25.5 mm
Device height	57.5 mm
Device depth	30 mm
Built-in depth	20.5 mm
Min. depth of built-in installation box	30 mm
Operating / setting temperature (Min-Max)	-5-40 °C
Storage temperature (Min-Max)	-5-40 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz

Label space/information surface	No
Lighting	No

Cable section (Min-Max)	4-4 mm ²
-------------------------	---------------------

Documentation

CATALOGUE PAGE & OTHERS

 [ex223001_0733.pdf](#) | PDF (0.08Mo)

Agreements & Certificates

 [OC / CB-CN53104](#) | (0.78Mo)