

Product sheet



SYNERGY™ LEGRAND

Synergy™ - Switch Grid module - 2 way retractive centre off - 20AX - 250V~ - White

REF. 735414 | EAN. 3245067354148

> [Visit e-catalogue](#)

Product characteristics

- Single pole switches 20 AX - 250 V~ - Conform to BS EN 60669 - 1 - White - 2 - way retractive centre off

Technical characteristics

Wiring system	Two-way switch
Method of operation	Rocker/button
Assembly arrangement	Basic element with central cover plate
Number of modules (module system)	1
Push button switch	No
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Engage (snap)
With mounting plate	No
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Glossy
Colour	White
RAL-number (similar)	9003

Function lighting	Other
Type of lighting	Other
Suitable for degree of protection (IP)	IP2X
degree of impact strength (IK)	IK01
Nominal voltage	250 V
Rated current	20 A
Switching current for fluorescent lamps	20 AX
Monitoring contact	No
Connection type	Screwed terminal
Device width	25.5 mm
Device height	57.5 mm
Device depth	30 mm
Built-in depth	20.5 mm
Min. depth of built-in installation box	30 mm
Operating / setting temperature (Min-Max)	-5-40 °C
Storage temperature (Min-Max)	-5-40 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz

Colour of switch operator	White
Label space/information surface	No
Lighting	No

Cable section (Min-Max)	4-4 mm ²
-------------------------	---------------------

Documentation

CATALOGUE PAGE & OTHERS

 [ex223001_0733.pdf](#) | PDF (0.08Mo)

Agreements & Certificates

 [OC / CB-CN53705](#) | (0.35Mo)