

Product sheet



SYNERGY™ LEGRAND

Synergy™ - SAT socket - single - "F" type - White

REF. 730041 | EAN. 3245067300411

[> Visit e-catalogue](#)

Product characteristics

- Synergy - telephone, data and TV sockets - white - Front plates : white thermoset - Terminal screws captive and backed off ready for cabling - large angled terminal entries - Compact mechanism for maximised wiring space - Supplied with faceplate screw caps
- TV sockets - For DVBT, Cablecast and satellite installation. UHD TV compatible - Class A shielded star sockets LTE Ready (4G protected) . Recommended coaxial cable : 17 VATC. Star cabling (1 socket = 1 cable to antenna, splitter or multiswitch) . Visual checking of the connection - Meet EN 50083 - 4 and EN 50083 - 2 European directive - TV : male connector (9.5 mm) - R : female connector (9.5 mm) - TV : 5 - 68 / 120 - 862 MHz - R : 87.5 - 108 MHz - SAT : 950 - 2400 MHz - 2 modules Single TV star sockets - TV F type

Technical characteristics

Model	End socket
Type of socket outlet	SAT
DAB+	No
Mounting method	Flush-mounted
Assembly arrangement	Basic element with full cover plate
Tap loss at 860 MHz	1 dB
Tap loss at 2150 MHz	1.5 dB
Number of outlets	1
Suitable for cable modem	No
Suitable for remote power supply	Yes
Colour	White
RAL-number (similar)	9003
Surface protection	Untreated

Surface finishing	Glossy
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Degree of protection (IP)	IP21
degree of impact strength (IK)	IK04
Device width	86 mm
Device height	86 mm
Device depth	33 mm
Min. depth of built-in installation box	40 mm
Operating / setting temperature (Min-Max)	5-45 °C
Storage temperature (Min-Max)	-25-70 °C

Documentation

TECHNICAL DOCUMENTATION



F00239EN-00.pdf | PDF (0.42Mo)