

Product sheet

**SYNERGY™ LEGRAND****Synergy™ - Double pole switch - Double pole red rocker - 45 A 250 V~ - 86x86 mm - White**

REF. 730122 | EAN. 3245067301227

[> Visit e-catalogue](#)

Product characteristics

- Synergy - double pole switches - white - Front plates : white thermoset - Terminal screws captive and backed off ready for cabling - large angled terminal entries - Compact mechanism for maximised wiring space - Supplied with faceplate screw caps
- Double pole switches 45 A - 250 V~ - Conform to BS EN 60669 - 1 - ASTA licence - For flush-mounting, back box to be min. 45 mm deep Nominal plate dimensions : 86 x 86 mm - DP switch red rocker marked COOKER

Technical characteristics

Wiring system	Switch 1-pole
Method of operation	Rocker/button
Assembly arrangement	Basic element with full cover plate
Push button switch	No
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic
Material quality	Duroplast
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Glossy
Colour	White

degree of impact strength (IK)	IK01
Nominal voltage	250 V
Rated current	45 A
Switching current for fluorescent lamps	45 AX
Monitoring contact	No
Connection type	Screwed terminal
Heating switch	No
Washing machine switch	Yes
Device width	86 mm
Device height	86 mm
Device depth	35 mm
Built-in depth	22 mm
Min. depth of built-in installation box	30 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No

RAL-number (similar)	9003
Colour of switch operator	Red
Label space/information surface	No
Lighting	No
Function lighting	Other
Type of lighting	Other
Suitable for degree of protection (IP)	IP2X

IFTTT support available	No
Operating / setting temperature (Min-Max)	-5-40 °C
Storage temperature (Min-Max)	-5-40 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz
Cable section (Min-Max)	10-10 mm ²

Documentation

Agreements & Certificates

-  OC / CB-FR_708126 | (0.6Mo)
-  LGRP-00491-V01.01-EN.pdf | PDF (0.56Mo)
-  ASTA-783 | (0.34Mo)