

Product sheet

**SYNERGY™ LEGRAND****Synergy™ - Single pole switch - 3 gang - 1 way - 10 AX
250 V~ - White**

REF. 730124 | EAN. 3245067301241

[> Visit e-catalogue](#)

Product characteristics

- Synergy - single pole switches, single pole push and key switches, rotary dimmers - white - Front plates : white thermoset - Terminal screws captive and backed off ready for cabling - large angled terminal entries - Compact mechanism for maximised wiring space - Supplied with faceplate screw caps
- Single pole plate switches 10 AX - 250 V~ - Conform to BS EN 60669 - 1 - For flush-mounting, back box to be min. 16 mm deep - ASTA licence Nominal plate dimensions : 86 x 86 mm - 3 gang - 1 way

Technical characteristics

Wiring system	Switch 1-pole
Method of operation	Rocker/button
Assembly arrangement	Basic element with full cover plate
Push button switch	No
Number of rockers	3
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic
Material quality	Duroplast
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Glossy
Colour	White

degree of impact strength (IK)	IK01
Nominal voltage	250 V
Rated current	10 A
Switching current for fluorescent lamps	10 AX
Monitoring contact	No
Connection type	Screwed terminal
Heating switch	No
Washing machine switch	No
Device width	86 mm
Device height	86 mm
Device depth	25.5 mm
Built-in depth	14 mm
Min. depth of built-in installation box	30 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No

RAL-number (similar)	9003
Colour of switch operator	White
Label space/information surface	No
Lighting	No
Function lighting	Other
Type of lighting	Other
Suitable for degree of protection (IP)	IP2X

Compatible with Amazon Alexa	No
IFTTT support available	No
Operating / setting temperature (Min-Max)	-5-40 °C
Storage temperature (Min-Max)	-5-40 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz
Cable section (Min-Max)	4-4 mm²

Documentation

TECHNICAL DOCUMENTATION

 F00223EN-03.pdf | PDF (0.59Mo)

Agreements & Certificates

 LGRP-2015-309-V1-EN.pdf | PDF (0.62Mo)

 OC / CB-FR_708093 | (0.72Mo)

 ASTA-781 | (0.4Mo)