

Product sheet

**SYNERGY™ LEGRAND****Synergy™ - Single pole switch - 1 gang - 1 way 20 AX
250 V~ - White**

REF. 730130 | EAN. 3245067301302

[> Visit e-catalogue](#)

Product characteristics

- Synergy - single pole switches, single pole push and key switches, rotary dimmers - white - Front plates : white thermoset - Terminal screws captive and backed off ready for cabling - large angled terminal entries - Compact mechanism for maximised wiring space - Supplied with faceplate screw caps
- Single pole plate switches 20 AX - 250 V~ - Conform to BS EN 60669 - 1 - For flush-mounting, back box to be min. 16 mm deep - Nominal plate dimensions : 86 x 86 mm - 1 gang - 1 way

Technical characteristics

Wiring system	Switch 1-pole
Method of operation	Rocker/button
Assembly arrangement	Basic element with full cover plate
Push button switch	No
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic
Material quality	Duroplast
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Glossy
Colour	White

Function lighting	Other
Type of lighting	Other
Suitable for degree of protection (IP)	IP2X
degree of impact strength (IK)	IK01
Nominal voltage	250 V
Rated current	20 A
Switching current for fluorescent lamps	20 AX
Monitoring contact	No
Connection type	Screwed terminal
Device width	86 mm
Device height	86 mm
Device depth	25.5 mm
Built-in depth	14 mm
Min. depth of built-in installation box	30 mm
Operating / setting temperature (Min-Max)	-5-40 °C

RAL-number (similar)	9003
Colour of switch operator	White
Label space/information surface	No
Lighting	No

Storage temperature (Min-Max)	-5-40 °C
Voltage type	AC
Frequency (Min-Max)	50-60 Hz
Cable section (Min-Max)	4-4 mm ²

Documentation

TECHNICAL DOCUMENTATION

 [F03162EN-00.pdf](#) | PDF (0.37Mo)

Agreements & Certificates

-  [ASTA-782](#) | (0.36Mo)
-  [OC / CB-FR_708093](#) | (0.72Mo)