

Product Data Sheet



ARTEOR LEGRAND

Arteor 1 Gang Intermediate 10AX Switch Round Magnesium

REF. 573164 | EAN. 3245065731644

> [Link to e-catalog product sheet](#)

Product description

- Mechanism supplied with integrated plastic cover and support frame
- To be equipped with surround plate

Technical recommendations

- Suitable for 25mm 1 gang box

Technical characteristics

| | |
|-------------------------|----------------------------------------|
| Wiring system | Intermediate switch |
| Method of operation | Rocker/button |
| Assembly arrangement | Basic element with central cover plate |
| Push button switch | No |
| Number of rockers | 1 |
| Mounting method | Flush-mounted |
| Type of fastening | Mounting with claw and screw |
| With mounting plate | No |
| Material | Plastic |
| Material quality | Thermoplastic |
| Halogen free | Yes |
| Antimicrobial treatment | No |
| Surface protection | Lacquered |
| Surface finishing | Matt |

| | |
|-----------------------------------------|------------------|
| Nominal voltage | 250 V |
| Rated current | 10 A |
| Switching current for fluorescent lamps | 10 AX |
| Monitoring contact | No |
| Connection type | Screwed terminal |
| Heating switch | No |
| Washing machine switch | No |
| Device width | 80 mm |
| Device height | 80 mm |
| Device depth | 31 mm |
| Built-in depth | 15 mm |
| Min. depth of built-in installation box | 30 mm |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |

| | |
|----------------------------------------|-------|
| Colour | Grey |
| Colour of switch operator | Grey |
| Label space/information surface | No |
| Lighting | No |
| Function lighting | Other |
| Type of lighting | Other |
| Suitable for degree of protection (IP) | IP40 |
| degree of impact strength (IK) | IK04 |

| | |
|-------------------------------------------|-----------|
| IFTTT support available | No |
| Operating / setting temperature (Min-Max) | -5-50 °C |
| Storage temperature (Min-Max) | -10-70 °C |
| Voltage type | AC |
| Frequency (Min-Max) | 50-60 Hz |
| Cable section (Min-Max) | 4-4 mm² |

Documents

Catalogue pages

 [wiring-accessories-2020-006.pdf](#) | PDF (0.12Mo)

Agreements & certificates

 [OC / CB-CN52912](#) | (0.29Mo)