

Product sheet



SYNERGY™ LEGRAND

Synergy™ - Socket outlet - 2 gang unswitched - 13 A
250 V~ - Metalclad

REF. 733875 | EAN. 3245067338759

> [Visit e-catalogue](#)

Product characteristics

- Synergy - British standard socket outlets and fused connection units - Metalclad - Front plates : grey epoxy coated steel - Terminal screws captive and backed off ready for cabling - large angled terminal entries - Supplied complete with close fit 43 mm deep surface - mounting back box
- Socket outlets 13 A - 250 V~ - Conform to BS 1363 - Part 2 : 1995 - With safety shutter mechanism - Flush-mounting back box : min. 25 mm deep - 2 gang unswitched - Nominal plate dimensions : 86 x 146 mm

Technical characteristics

Model	British Standard	Material	Metal
Concurrently switching neutral conductor	No	Material quality	Other
Protective contact	Flat	Halogen free	Yes
Number of active contacts (round)	0	Surface protection	Lacquered
Number of active contacts (flat)	4	Surface finishing	Matt
Number of active contacts (square)	0	Antimicrobial treatment	No
Assembly arrangement	Basic element with full cover plate	With loop through function	Yes
With complementary luminous signal	No	With on/off switch	No
Number of ports USB-A	0	Rotated central insert	No
Number of ports USB-C	0	Nominal current	13 A
Number of socket outlets	2	Nominal voltage	250 V
Number of modules (module system)	4	Frequency (Min-Max)	50-60 Hz
Number of socket outlets switchable	2	Suitable for degree of protection (IP)	IP2X
Number of phases	1	degree of impact strength (IK)	IK01
Imprint/indication	Other	Device width	146 mm

Connection type	Screwed terminal	Device height	86 mm
With hinged lid	No	Device depth	47.4 mm
With enhanced contact protection	Yes	Compatible with Apple HomeKit	No
Label space/information surface	No	Compatible with Amazon Alexa	No
Colour	Grey	Compatible with Google Assistant	No
Metallic colour	Yes	IFTTT support available	No
Transparent	No	With Wi-Fi signal repeater	No
Lockable	No	With built-in bluetooth speaker	No
Eject-mechanism	No	For heavy conditions according to VDE	No
Insulated mounting	No	Built-in depth	0 mm
With function lighting	No	Operating / setting temperature (Min-Max)	-5-40 °C
With orientation lighting	No	Storage temperature (Min-Max)	-5-40 °C
Overvoltage protection	No	Voltage type	AC
Fault current protection	No	Power Delivery	No
With miniature fuse	No	Cable nature for connection	Flexible or rigid
Special power supply	None	Cable section (Min-Max)	4-4 mm ²
Mounting method	Surface mounted	Cable support	Other
Type of fastening	Mounting with screw	Connected object	No

Documentation

Agreements & Certificates

-  G-MARK-0048-1240 R 1 | (1.99Mo)
-  ASTA-780 | (0.28Mo)
-  AoC-2566AS04ARLI59414 | (0.37Mo)