

Arteor™

ventilation, heating, roller blinds control, RCBO and MCB



Support frame and plate selection charts **p. 86-93**

Mechanisms supplied with rocker plates, to be equipped with support frames (p. 75) and plates (p. 76-85)

Pack	Cat.Nos	Fan controllers	Pack	Cat.Nos	Electric roller blind controllers - 250 V~
		2 modules			For control via automatic box (N/O mechanism)
		AC speed control - 4 positions			Double push-button - 10 A
1	5 722 17	○ White	10	5 722 19	2 modules
1	5 727 17	● Magnesium	10	5 727 19	○ White - square version
		Rotary speed controller for fan	10	5 732 19	● Magnesium - square version
		Operates 40 to 400 VA limit switch	10	5 737 19	○ White - round version
		For progressive speed control of ceiling fan	10	5 737 19	● Magnesium - round version
1	5 722 18	○ White			For direct control of a motor (mechanism with fixed positions)
1	5 727 18	● Magnesium			Double push-button - 10 A
		Fan step regulator - 100 W			2 modules
5	5 722 15	○ White	10	5 722 20	○ White - square version
5	5 727 15	● Magnesium	10	5 727 20	● Magnesium - square version
		Thermostats	10	5 732 20	○ White - round version
		Electronic room thermostat	10	5 737 20	● Magnesium - round version
		Control knob with index and adjustable segments for min. and max. settings			RCBO - 16 A - 230 V~
		Adjustable range from 5 °C to 30 °C (+/- 0.5 °C)			Single pole + Neutral - 30 mA - 2 modules
		Power supply: 230 V~ - 50/60 Hz			The RCBO is used to protect people (premises with a conductive floor, presence of water, etc...) against direct contact with live parts or leakages to earth
		One potential free changeover contact output			With test button
		Suitable for controlling heated ceilings and underfloor heating	1	5 723 60	○ White
		- LV use breaking capacity:			Thermal magnetic proximity MCB
		8 A - 250 V~ - resistive inductive circuit			Single pole + Neutral - 230 V~ - 16 A
		2 A - 250 V~ - inductive circuit			Used for local protection of part in a circuit (e.g. 2P+E socket) against overloads and short-circuits
		- ELV use breaking capacity:			Main protection being close to the user plus discriminating allows immediate reset
		12 to 48 V~ - 12 to 24 V~, from 1 mA min. to 500 mA max.			Can also be used as a local consumption limiter (depending on its rating)
		2 modules			Breaking capacity: 3000 A - 2 modules
1	5 722 03	○ White	1	5 723 61	○ White
1	5 727 03	● Magnesium			
		Thermostat for electric floor heating			
		With one potential free N/O contact and LED			
		16 A - 230 V~			
		Adjustable range from 10 °C to 60 °C			
		2 modules			
1	5 722 63	○ White			
1	5 727 63	● Magnesium			
		Curtain switches			
		1 module			
		Curtain switch centre off			
5	5 722 02	○ White			
5	5 727 02	● Magnesium			
		Curtain switch centre retract			
5	5 722 01	○ White			
5	5 727 01	● Magnesium			