

Arteor™ dimmers square version



Support frame and plate selection charts **p. 414-421**
Load selection charts **p. 389**

Mechanisms supplied with rocker plates, to be equipped with support frames (p. 411) and plates (p. 414 to 421)
100/240 VA - 50/60 Hz

Pack	Cat.Nos	Resistive/inductive loads touch dimmers	Pack	Cat.Nos	Universal dimmers
1 1	5 722 11 5 727 11	Without neutral, 2-wire Push-button dimmer - 600 W To be installed alone in a 3 module box with a 3-module support frame and a 2-module plate ○ White - 2 modules ● Magnesium - 2 modules	1 1	5 722 39 5 727 39	Without neutral, 2 wires Push-button dimmer for all types of lamps: - Dimmable LEDs: 150 W - Dimmable compact fluorescent lamps: 150 W - Halogen with transformer: 400 VA - Fluorescent tube: 200 VA - Halogen 230 V and incandescent: 400 W Can be associated with one or several push-buttons without neon, for ON/OFF or dimming control Lights come on again at the same lighting level as before they were last switched off ○ White - 2 modules ● Magnesium - 2 modules
1 1	5 722 13 5 727 13	Leading edge dimmers Without neutral, 2-wire Rotary dimmer - 400 W ○ White - 2 modules ● Magnesium - 2 modules	1 1	5 722 38 5 727 38	Dimmers 0-10 V Push-button dimmer for ballasts 0-10 V ○ White - 2 modules ● Magnesium - 2 modules
1 1	5 735 01 5 737 01	Rotary dimmer - 1000 W To be installed alone in a 3 module box with a 3-module support frame and a 2-module plate Not CE compliant ○ White - 2 modules ● Magnesium - 2 modules	1 1	5 740 10 ¹ 5 740 60 ²	Lighting environment controller Main controller 3 x 1000 W (the cumulative load of the 3 circuits must not exceed 2200 W) Supplied complete with flush-mounting box, support frame and plate Particularly suitable for controlling lighting environments in conference rooms, meeting rooms, restaurants, showrooms, etc. Possible applications: - control of 3 lighting circuits in one room - control of lighting environments by dimming polychromatic lamps (red/green/blue or warm/white/cold white) Controls on front face: - 6 push-buttons for on/off/dimming control of each of the 3 lighting circuits - 3 sets of 5 LEDs displaying the current level of each circuit - 4 push-buttons for memorisation and control of lighting environments ○ White ● Magnesium
1 1	5 740 07 5 740 57	Trailing/leading edge dimmers Push-button dimmer - 2 x 400 W With Magnesium control touch Supplied with support frame ○ White - 2 modules ● Black - 2 modules	1 1	5 722 41 ¹ 5 727 41 ²	1: Supplied with White plate 2: Supplied with Mirror Black plate
1 1	5 740 06 5 740 56	Push-button dimmer - 600 W To be installed alone in a 3 module box with a 3-module support frame and a 2-module plate ○ White - 2 modules ● Magnesium - 2 modules	1 1	5 722 41 ¹ 5 727 41 ²	
1 1	5 722 41 ¹ 5 727 41 ²	Push-button dimmer - 1000 W Supplied complete with flush-mounting box, support frame and plate 5 LEDs showing lighting intensity status ○ White - 5 vertical modules ● Magnesium - 5 vertical modules	1 1	5 722 41 ¹ 5 727 41 ²	