

Synergy® modern
fused connection units



7310 35



7312 34



7310 30



7312 32



7310 37




7312 36



7310 31



7312 33



Front plates : clip on die cast plate with high quality satin finish; anthracite interiors; matching decorative rockers (except where indicated)
Terminal screws captive and backed off ready for cabling

Pack	Cat. Nos.		Fused connection units 13 A - 250 V~	
			Conform to BS 1363 - Part 4 : 1995 Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm	
			Switched	
1	7310 34	7312 34		Switched, DP
1	7310 35	7312 35		Switched, DP + red LED power indicator
1	7310 36	7312 36		Switched, DP with cord outlet
1	7310 37	7312 37		Switched, DP with cord outlet + red LED power indicator

Pack	Cat. Nos.		Fused connection units 13 A - 250 V~ (continued)	
			Conform to BS 1363 - Part 4 : 1995 Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm	
			Unswitched	
1	7310 30	7312 30		Unswitched
1	7310 31	7312 31		Unswitched + red LED power indicator
1	7310 32	7312 32		Unswitched with cord outlet
1	7310 33	7312 33		Unswitched with cord outlet + red LED power indicator

Synergy® modern control switches



7310 10



7312 12



7310 23



7312 22



Flush mounting
back boxes

p. 187



7310 16



7312 14



7310 29

Red LED power indicator



Front plates : clip on die cast plate with high quality satin finish; anthracite interiors; matching decorative rockers (except where indicated)
Terminal screws captive and backed off ready for cabling

Pack	Cat. Nos.		Double pole switches 20 A - 250 V~	
			Conform to BS EN 60669-1 : 2000 Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm	
1	7310 10	7312 10		20 A DP
1	7310 14	7312 14		20 A DP with cord outlet
1	7310 16	7312 16		20 A DP with cord outlet + red LED power indicator
1	7310 12	7312 12		20 A DP + red LED power indicator

Pack	Cat. Nos.		Cable outlets 20 A - 250 V~	
			Conform to BS 5733 : 1995 Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 86 x 86 mm	
1	7310 19	7312 19		20 A – with terminal block and outlet gland

Pack	Cat. Nos.		Double pole switches 45 A - 250 V~	
			Conform to BS EN 60669-1 : 1995 Red rocker Flush mounting back box : min. 48 mm deep Nominal plate dimensions : 89 x 89 mm	
1	7310 22	7312 22		45 A DP
1	7310 23	7312 23		45 A DP with red power indicator
			Nominal plate dimensions : 146 x 86 mm	
1	7310 21	7312 21		45 A DP with red power indicator Stainless steel plate with fixing screws

Pack	Cat. Nos.		Cooker control units 45 A - 250 V~	
			Conform to BS 4177 : 1992 Red rocker Flush mounting back box : min. 47 mm deep Nominal plate dimensions : 89 x 149 mm	
1	7310 29	7312 29		45 A DP switch + 13 A DP switched socket outlet

Pack	Cat. Nos.		Cable outlets 45 A - 250 V~	
			Conform to BS 5733 : 1995 2 piece design for safety Stainless steel plate with fixing screws Flush mounting back box : min. 48 mm deep Nominal plate dimensions : 86 x 86 mm	
1	7310 26	7312 26		45 A – with terminal block