

# Synergy® traditional control switches



7330 14




7332 10



7330 22



7332 22

Flush and surface mounting back boxes **p. 187**

7330 12



7332 16



7330 23



7332 29



Red LED power indicator

Brushed stainless steel front plates : brushed stainless steel with clear epoxy satin lacquer coating  
 Polished stainless steel front plates : electroplated stainless steel plate with trivalent chrome for mirror finish  
 White interiors and rockers (red rockers for specific items)  
 Terminal screws captive and backed off ready for cabling

Pack	Cat. Nos.		Double pole switches 20 A - 250 V~	
	Stainless steel		Conform to BS EN 60669-1 : 2000	
	Brushed	Polished	Flush mounting back box : min. 25 mm deep	
			Nominal plate dimensions : 86 x 86 mm	
1	7330 10	7332 10		20 A DP
1	7330 14	7332 14		20 A DP with cord outlet
1	7330 16	7332 16		20 A DP with cord outlet + red LED power indicator
1	7330 12	7332 12		20 A DP with red LED power indicator

Pack	Cat. Nos.		Cable outlets 20 A - 250 V~	
	Stainless steel		Conform to BS 5733 : 1995	
	Brushed	Polished	Flush mounting back box : min. 25 mm deep	
			Nominal plate dimensions : 86 x 86 mm	
1	7330 19	7332 19		20 A - with terminal block and outlet gland

Pack	Cat. Nos.		Double pole switches 45 A - 250 V~	
	Stainless steel		Conform to BS EN 60669-1 : 2000	
	Brushed	Polished	Red rocker	
			Flush mounting back box : min. 48 mm deep	
			Nominal plate dimensions :	
			2 gang - 146 x 86 mm	
			1 gang - 86 x 86 mm	
1	7330 20	7332 20		45 A DP
1	7330 21	7332 21		45 A DP with red LED power indicator
1	7330 22	7332 22		45 A DP
1	7330 23	7332 23		45 A DP with red LED power indicator

Pack	Cat. Nos.		Cooker control units 45 A - 250 V~	
	Stainless steel		Conform to BS 4177 : 1992	
	Brushed	Polished	45 A - 250 V~ DP switch with 13 A - 250 V~ DP switched socket outlet	
			Red rocker	
			Flush mounting back box : min. 48 mm deep	
			Nominal plate dimensions : 86 x 146 mm	
1	7330 28	7332 28		DP with DP switched socket
1	7330 29	7332 29		DP with DP switched socket + red LED power indicators

Pack	Cat. Nos.		Cable outlets 45 A - 250 V~	
	Stainless steel		Conform to BS 5733 : 1995	
	Brushed	Polished	2 piece design for safety	
			Flush mounting back box : min. 48 mm deep	
			Nominal plate dimensions : 86 x 86 mm	
1	7330 26	7332 26		45 A - with terminal block

# Synergy® traditional


TV, telephone and data sockets



7330 43



7332 42



Flush and surface mounting back boxes **p. 187**



7330 50



7332 57



8201 43

Brushed stainless steel front plates : brushed stainless steel with clear epoxy satin lacquer coating  
 Polished stainless steel front plates : electroplated stainless steel plate with trivalent chrome for mirror finish  
 White interiors and rockers  
 Terminal screws captive and backed off ready for cabling

Pack	Cat. Nos.		TV, radio and satellite sockets
	Stainless steel		Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 86 mm
	Brushed	Polished	
1	7330 40	7332 40	Screened TV – single, male Non-isolated
1	7330 41	7332 41	Screened satellite – single, 'F' type
1	7330 42	7332 42	Screened TV + FM Isolated
1	7330 43	7332 43	Screened TV + FM + satellite, 'F' type
1	7330 45 <sup>1</sup>	7332 45 <sup>1</sup>	Quad outlet, TV, radio + 2 satellite + TV return with secondary telephone outlet <sup>2</sup>

Pack	Cat. Nos.		Telephone sockets
	Stainless steel		Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 86 mm
	Brushed	Polished	
1	7330 50 <sup>1</sup>	7332 50 <sup>1</sup>	Single master
1	7330 51 <sup>1</sup>	7332 51 <sup>1</sup>	Single secondary
1	7330 54	7332 54	Single RJ11/12

Pack	Cat. Nos.		Data sockets
	Stainless steel		CAT 6 compliant UTP Rapid cable connection
	Brushed	Polished	Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 86 mm
1	7330 56	7332 56	RJ45 – single
1	7330 57	7332 57	RJ45 – double

Pack	Cat. Nos.		Media plates (monobloc)
	Stainless steel		Comprising 2 x independent satellite feeds, 1 x terrestrial TV socket suitable for analogue and digital signals, 1 x video return, 1 x secondary telephone point, 2 x Synergy 2 gang switched DP 13 A sockets To be used with back box Cat. No. 8204 58 below Dimensions : 206 x 267 mm Material : stainless steel
	Brushed	Polished	
1	8201 43	8201 44	Media plate

Pack	Cat. Nos.	Back box for media plate
1	8204 58	Dimensions : 194 x 254 x 35 mm With phase barrier Material : grey epoxy coated steel 35 mm deep box

1 : Not suitable for use in the ROI  
 2 : Stainless steel plate with fixing screws