

Synergy® modern

switches and dimmers



Front plates : clip on die cast plate with high quality satin finish; anthracite interiors; matching decorative rockers (except where indicated)
Terminal screws captive and backed off ready for cabling
Hidden screws

Pack	Cat. Nos.		Single pole plate switches 10 AX - 250 V~	
			Conform to BS EN 60669-1 : 2000 Flush mounting back box : min. 16 mm deep Nominal plate dimensions : 89 x 89 mm 1, 2 and 3 gang - 89 x 89 mm 4 and 6 gang - 89 x 149 mm	
1	7310 00	7312 00		1 gang - 1 way
1	7310 01	7312 01		1 gang - 2 way
1	7310 05	7312 05		1 gang - intermediate
1	7310 02	7312 02		2 gang - 2 way
1	7310 03	7312 03		3 gang - 2 way
1	7310 04	7312 04		4 gang - 2 way

Pack	Cat. Nos.		Single pole plate switches 20 AX - 250 V~	
			Conform to BS EN 60669-1 : 2000 Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm	
1	7311 31	7313 31		1 gang - 2 way
1	7311 32	7313 32		2 gang - 2 way
1	7311 33	7313 33		3 gang - 2 way

Pack	Cat. Nos.		Single pole push switches 10 A - 250 V~	
			Conform to BS EN 60669-1 : 2000 Flush mounting back box : min. 16 mm deep Nominal plate dimensions : 89 x 89 mm	
1	7310 07	7312 07		1 gang - 2 way push switch

Pack	Cat. Nos.		Dimmer units - 230 V~	
			Conform to BS EN 60669-2-1 : 2000 Not suitable for fluorescent load Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm Dimmers for use with tungsten filament lamps, GU10 halogen lamps and low voltage systems using appropriate transformer	
1	7310 46	7312 46		1 gang - 2 way 50 Hz 40 W-250 W push on/off rotary
1	7310 47	7312 47		2 gang - 2 way 50 Hz 40 W-250 W push on/off rotary

Pack	Cat. Nos.		Dimmer units - 230 V~ - electronic type	
			Conform to BS EN 60669-2-1 : 2000 Not suitable for fluorescent load Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm Dimmers for use with tungsten filament lamps, good quality wire-wound transformers for low voltage loads	
1	7311 56	7313 56		1 gang - 2 way 50-60 Hz 40 W-400 W push on/off rotary
1	7311 57	7313 57		2 gang - 2 way 50-60 Hz 40 W-400 W push on/off rotary

Pack	Cat. Nos.		3 pole fan switches 10 A - 250 V~	
			Conform to BS EN 60669-1 : 2000 White rocker with integrated padlockable safety block in OFF position Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 89 x 89 mm	
1	7310 09	7312 09		3 pole fan switch