



# ARD-R90 - iCLASS Reader - APR/EMEA



- ▶ **Contact less smart card reader, read only, long range**
- ▶ **Proximity/long range reader with beeper and multicolored LED display**
- ▶ **Rugged, weatherized polycarbonate enclosure, designed to withstand harsh environments**

Non-contact access control readers in 13.56 MHz technology (based on ISO 15693) for connecting to an access controller with Wiegand interfaces.

## Functions

Reads all iCLASS and ISO 15693 (CSN) compatible cards. "Parking Hold" feature allows connection to a loop detector to ensure accurate detection of vehicles in parking lanes.

Two ARD R90 units can operate one meter apart for "HI-LO" truck and car installations. iCLASS proximity cards that work with diversified keys of 64-bit length for two-way authentication, encrypted data is transmitted between the reader and card.

Beeper and multicolored LED display controlled internally or by host.

## Installation/Configuration Notes

- Cable length 150 m (500 ft).
- Power supply installation always closed to the reader.

- Please follow the general mounting instructions for the proximity reader regarding the distance between readers and metallic surfaces.

**Note** The Wiegand reader interface of the AMC2 4W does not provide sufficient power for the ARD R90. Please plan an external power supply for the ARD R90.

## Parts Included

- 1 Reader body with board
- 1 Mounting material
- 1 Installation guide

## Technical Specifications

### Housing

External dimensions (W x H x D)	30,48 x 30,48 x 3,175 cm (12 x 12 x 1.25 inch)
Material	Polycarbonate (UL 94)
Color	Black
Weight	1860 g (60 oz)

### Connections

Display	Multicolored LED
---------	------------------

**Housing**

Interfaces	Wiegand
------------	---------

**Environment conditions**

Operating temperature	-35° to 65°C (-31° to 150°F)
Humidity	5 to 95% no condensation water
Environment class	IP55

**Electrical parameters**

Power supply	12 – 24 VDC reserve voltage protected (linear supply recommended)
Current consumption (Avg/Peak)	480/1800 mA (12 VDC) 230/900 mA (24 VDC)
Reading process	iCLASS
Operating/modulation frequency	13.56 MHz
Reading distance	45 cm (17.72 in) with iCLASS card 22,9 cm (9.01 in) with iCLASS key/tag
Cable distance	150 m (500 ft)
Recommended cable	ALPHA 1295 (22 AWG)

**Ordering Information****ARD-R90 - iCLASS Reader - APR/EMEA**

Proximity long range access control reader  
with Wiegand interface.

**ARD-R90-AKT00**

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6258 5511  
Fax: +65 6571 2698  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**