

Fiber Optic, Wall Mounted Enclosure, Fiber Distribution Box, FDB-24

Features and benefits

- Compact and light weight for indoor or outdoor use
- Holds 24 mechanical or fusion splices plus 3 splitters
- Two PG16 ports with up to 24 SC adapters inside
- Lockable cover
- 2011/65/EU RoHS compliant and halogen free
- IP55 rated performance
- Material: light gray ABS plastic
- Dimensions: 13H x 9W x 3.5D inches (330H x 230W x 88D mm)



Description

The FDB-24 provides 8, 16 or 24 SC ports in a traditional two-layer design – a rear splice area for cable slack and splice protection, and a front interconnect area for SC ports.

The FDB-24 is suitable for indoor or outdoor FTTx applications that support up to 24 subscribers. It has a compact, light-weight wall-mountable housing with a weatherproof gasket and two PG16 weatherproof cable entry/exit ports. It easily accommodates 3 splitters, 24 splices and 24 SC ports.

Ordering information

FDB-24 _____

1

2

1. Adapter type
 SCA = SC/APC
 SCU = SC/UPC

2. Port type
 Blank = 24 port adapters only (no pigtails)
 08 = 8 port 8 pigtails and adapters
 16 = 16 port 16 pigtails and adapters
 24 = 24 port 24 pigtails and adapters
 3x108 = 24 port 3x(1x8) PLC splitters
 108 = 8 port 1x8 PLC splitter
 2x104 = 8 port 2x(1x4) PLC splitters
 208 = 8 port 2x8 PLC splitter
 116 = 16 port 1x16 PLC splitter
 2x108 = 16 port 2x(1x8) PLC splitters
 216 = 16 port 2x16 PLC splitter
 (PLC splitters have connectorized outputs)

