🇨🇭 Swiss Standard

Chrome wall mounted distribution box IP65

600x320x200mm
for 12xsplice trays

Dätwyler

Product information

Application

Connection from Fibre optic OPGW cables to buried cables
Outdoor applications
Area of application according specification IP65

Features

Splice- or connecting box according specification IP65
Very solid and well protected construction with big advantages for connecting fibre optic OPGW cables to buried cables.
Easy, fibre optic connecting solution for up to 120 fibres in a chrome wall mounted distribution box.
All inserts are designed for DWDM transmission with 10Gb.
The well established supporting tool for the ONT splice trays fits optimally.
The chrome wall mounted distribution box can be delivered with a KABA - or Keso locking system, e.g. 6 splice trays 72fibres and 24 connectors LSH- for carrier access.
On request with heat shrink tubing or screwed cable gland.

Construction

Size: 600x320x200mm (HxWxD)

- Chrome wall mounted distribution box 600x320x200mm for 12 splice trays ONT
  (1 connector plate amount the space of 2 splice trays)
- 2 pairs of fastener for 4 splice trays ONT at Pos.1 and 2 mounted
- Document bracket for A4 inside the front door fixed
- Clamp composed of: 3x woodscrew 6x50mm, 3x nylon dowel
  8mm and 3x M6 U-shim

Article No.	Description	Size
		HxWxD [mm]
184 848	Chrome wall mounted distribution box IP65	600 x 320 x 200

Technical changes reserved.