

FO patch panel OV-A

19"/1U, loaded

splice box with adapters and pigtails



Fibre optic splice box OV-A, 19"/1U, extractable,
configuration example with 24 SCD adapters and 48 pigtails

PRODUCT INFORMATION

| | | |
|--------------------------|---|---|
| APPLICATION | For the termination of fibre optic cables - maximum of 48 fibres. Loaded with FO adapters, ready for splicing prepared pigtails (2 m, colour code: IEC 60304), splice trays, splice holders and splice protection in crimp technology. | |
| DESCRIPTION | Housing: | metallic, extractable drawer with locking mechanism, can be upgraded to OV-AT using telescopic slides: allows for depth-adjustable mounting of box (5 steps, maximum 50 mm) |
| | Colour: | similar to RAL 7035 |
| | Imprint: | numbers (silk screen printing) on frontplate |
| | Capacity: | up to 48 fibres |
| | Strain relief: | with cable tie and screwed cable gland (M20) |
| | Cable entry: | rear left and right |
| | Dimensions: | 19"/1U, depth 254 mm |
| CONNECTOR SYSTEM | Adapter: | SCD, LCD, LSH, ST |
| SCOPE OF DELIVERY | Included are: - coloured pigtails with measurement report - FO adapters, fastened by screws - splice trays with cover - splice protection in crimp technology - splice holder - fastening set | |
| NOTE | Variants on request | |

FO patch panel OV-A

19"/1U, loaded

splice box with adapters and pigtails

PRODUCT INFORMATION

| Article No. | Description | Loaded with | |
|-------------|-----------------------------------|--|---|
| 190968 | Splice box, OV-A, extractable, 1U | 6x LCD adapter, blue polymer housing | with ceramic sleeve and 12 LC pigtails 2 m E09/125µm OS2 |
| 190969 | Splice box, OV-A, extractable, 1U | 6x LCD adapter, beige polymer housing | with ceramic sleeve and 12 LC pigtails 2 m G50/125µm OM2 |
| 190884 | Splice box, OV-A, extractable, 1U | 6x LCD adapter, turquoise polymer housing | with ceramic sleeve and 12 LC pigtails 2 m G50/125µm OM3 |
| 190975 | Splice box, OV-A, extractable, 1U | 12x LCD adapter, blue polymer housing | with ceramic sleeve and 24 LC pigtails 2 m E09/125µm OS2 |
| 190988 | Splice box, OV-A, extractable, 1U | 12x LCD adapter, beige polymer housing | with ceramic sleeve and 24 LC pigtails 2 m G50/125µm OM2 |
| 190885 | Splice box, OV-A, extractable, 1U | 12x LCD adapter, turquoise polymer housing | with ceramic sleeve and 24 LC pigtails 2 m G50/125µm OM3 |
| 191761 | Splice box, OV-A, extractable, 1U | 24x LCD adapter, blue polymer housing | with ceramic sleeve and 48 LC pigtails 2 m E09/125µm OS2 |
| 191762 | Splice box, OV-A, extractable, 1U | 24x LCD adapter, beige polymer housing | with ceramic sleeve and 48 LC pigtails 2 m G50/125µm OM2 |
| 191763 | Splice box, OV-A, extractable, 1U | 24x LCD adapter, turquoise polymer housing | with ceramic sleeve and 48 LC pigtails 2 m G50/125µm OM3 |
| 190989 | Splice box, OV-A, extractable, 1U | 6x LSH/APC adapter, green polymer housing | with ceramic sleeve and 6 LSH/APC pigtails 2 m E09/125µm OS2 |
| 190990 | Splice box, OV-A, extractable, 1U | 6x LSH adapter, black polymer housing | with ceramic sleeve and 6 LSH pigtails 2 m G50/125µm OM3 |
| 190893 | Splice box, OV-A, extractable, 1U | 12x LSH/APC adapter, green polymer housing | with ceramic sleeve and 12 LSH/APC pigtails 2 m E09/125µm OS2 |
| 190886 | Splice box, OV-A, extractable, 1U | 12x LSH adapter, black polymer housing | with ceramic sleeve and 12 LSH pigtails 2 m G50/125µm OM3 |
| 190894 | Splice box, OV-A, extractable, 1U | 24x LSH/APC adapter, green polymer housing | with ceramic sleeve and 24 LSH/APC pigtails 2 m E09/125µm OS2 |
| 190887 | Splice box, OV-A, extractable, 1U | 24x LSH adapter, black polymer housing | with ceramic sleeve and 24 LSH pigtails 2 m G50/125µm OM3 |
| 190888 | Splice box, OV-A, extractable, 1U | 6x SCD adapter, blue polymer housing | with ceramic sleeve and 12 SC pigtails 2 m E09/125µm OS2 |
| 190974 | Splice box, OV-A, extractable, 1U | 6x SCD adapter, beige polymer housing | with PB sleeve and 12 SC pigtails 2 m G50/125µm OM2 |
| 190882 | Splice box, OV-A, extractable, 1U | 6x SCD adapter, turquoise polymer housing | with PB sleeve and 12 SC pigtails 2 m G50/125µm OM3 |
| 190889 | Splice box, OV-A, extractable, 1U | 12x SCD adapter, blue polymer housing | with ceramic sleeve and 24 SC pigtails 2 m E09/125µm OS2 |
| 190955 | Splice box, OV-A, extractable, 1U | 12x SCD adapter, beige polymer housing | with PB sleeve and 24 SC pigtails 2 m G50/125µm OM2 |
| 190883 | Splice box, OV-A, extractable, 1U | 12x SCD adapter, turquoise polymer housing | with PB sleeve and 24 SC pigtails 2 m G50/125µm OM3 |
| 190973 | Splice box, OV-A, extractable, 1U | 24x SCD adapter, blue polymer housing | with ceramic sleeve and 48 SC pigtails 2 m E09/125µm OS2 |
| 190972 | Splice box, OV-A, extractable, 1U | 24x SCD adapter, beige polymer housing | with PB sleeve and 48 SC pigtails 2 m G50/125µm OM2 |
| 190991 | Splice box, OV-A, extractable, 1U | 24x SCD adapter, turquoise polymer housing | with PB sleeve and 48 SC pigtails 2 m G50/125µm OM3 |
| 190971 | Splice box, OV-A, extractable, 1U | 6x ST adapter, metal housing | with ceramic sleeve and 6 ST pigtails 2 m E09/125µm OS2 |
| 191757 | Splice box, OV-A, extractable, 1U | 6x ST adapter, metal housing | with PB sleeve and 6 ST pigtails 2 m G50/125µm OM2 |
| 191758 | Splice box, OV-A, extractable, 1U | 6x ST adapter, metal housing | with PB sleeve and 6 ST pigtails 2 m G50/125µm OM3 |
| 191759 | Splice box, OV-A, extractable, 1U | 12x ST adapter, metal housing | with ceramic sleeve and 12 ST pigtails 2 m E09/125µm OS2 |
| 191760 | Splice box, OV-A, extractable, 1U | 12x ST adapter, metal housing | with PB sleeve and 12 ST pigtails 2 m G50/125µm OM2 |
| 190880 | Splice box, OV-A, extractable, 1U | 12x ST adapter, metal housing | with PB sleeve and 12 ST pigtails 2 m G50/125µm OM3 |
| 190999 | Splice box, OV-A, extractable, 1U | 24x ST adapter, metal housing | with ceramic sleeve and 24 ST pigtails 2 m E09/125µm OS2 |
| 191764 | Splice box, OV-A, extractable, 1U | 24x ST adapter, metal housing | with PB sleeve and 24 ST pigtails 2 m G50/125µm OM2 |
| 190881 | Splice box, OV-A, extractable, 1U | 24x ST adapter, metal housing | with PB sleeve and 24 ST pigtails 2 m G50/125µm OM3 |

All pigtails are coloured (in accordance with IEC 60304), stripped and stored in splice tray