HP 27fw with Audio Display



Impossibly thin. Irresistibly priced.

Get the crisp picture quality you crave with this ultra-slim, micro-edge display, immersive ultra-wide viewing angles and built-in audio. From browsing content to streaming entertainment—it allows you to see your world in a whole new way.



Appealing, ultra-thin design

Built from aluminum with a matte finish and high-polished resin, this ultra-slim display brings home a modern look and feel without the premium price tag.

Stunning from edge-to-edge

With its vivid IPS panel, this FHD¹ resolution micro-edge display delivers ultra-wide viewing angles and crisp, clear picture quality. It's an expansive viewing experience, perfect for dual display setups.

Fully integrated audio

Immerse yourself in great sound without cluttering your desk with the messy cords and external speakers. Powerful built-in audio paired with crisp FHD resolution make this display the full entertainment package.

¹ Full high-definition (FHD) content required to view FHD images.

HP 27fw with Audio Display

Featuring

FHD display / 1080p display

Brilliant visuals and unforgettable quality from a stunning FHD display.

Micro-edge display

Micro-edge design creates a larger viewing experience.

Step up to the best

IPS technology brings you clear views from almost any angle. Every seat is the best seat in the house.

Virtually edge-to-edge panel

A virtually edge-to-edge panel means maximized screen area and expansive entertainment.

AMD® FreeSync™ technology

Makes display stutter, input lag, and screen tears ancient history.

Share the panoramic view

Ultra-wide 178° angle viewing with consistent detail and vibrant color.

Compact, sleek design

Slim design and single connection gives you more room for an enhanced computing experience.

Anti-glare panel

Enjoy the sun and your favorite content with this anti-glare panel.

Modern design

Sleek design that seamlessly integrates with the modern home.

HP 27fw with Audio Display







Display colors	Display size	68.58 cm (27")
Display to pitch PS with LED backlight O.311 mm	Display colors	Up to 16.7 million colors supported (through FRC technology)
Pote pitch 178 horizontal, 178 vertical 178 horizontal, 178 hori	Aspect ratio	16:9 ¹
Horizontal Viewing angle 178° horizontal; 178° vertical Tit: 5 Tit: 5 to 25° Response time 5 ms gray to gray (with overdrive) ¹ Brightness 300 cffm²¹ Contrast ratio 1000:1 static; 10000000:1 dynamic ¹ Product color Bitizzard white Resolutions supported 800 x 600 1000:1 static; 10000000:1 dynamic ¹ Product color Bitizzard white Resolutions supported 800 x 600 1000:1 static; 10000000:1 dynamic ¹ Product color Bitizzard white Resolutions supported 800 x 600 1000:1 static; 10000000:1 dynamic ¹ Product color Bitizzard white Resolutions supported 800 x 600 1000 x 1000	Display type	IPS with LED backlight
Tilt Tilt 5 to +25° Response time 5 ms gray to gray (with overdrive) ¹ Response time 5 ms gray to gray (with overdrive) ¹ Rightness 300 cd/m² ² Contrast ratio 10001 static; 10000000:1 dynamic ¹ Product color 8ilizzard white 100024 x768; 1280 x 1024; 1280 x 720; 1280 x 800; 1366 x 768; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 640 x 480; 720 x 400; 800 x 600 x	Pixel pitch	0.311 mm
Response time 5 ms gray to gray (with overdrive) 1 Brightness 30 or c/m² 1 Contrast ratio 1000.1 static; 100000000:1 dynamic 1 Product color Bitzard white Resolutions supported 1026x y 1568 1280 x 1024; 1280 x 720; 1280 x 800; 1366 x 768; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 640 x 480; 720 x 400; 1000 x 600 x 60	Horizontal viewing angle	178° horizontal; 178° vertical
Brightness 300 cd/ms² 1 Contrast ratio 1000:1 static; 100000001 dynamic ¹ Product color Bizzard white Resolutions supported 812zard white Resolutions supported 300 x 600 300 x 600 Bizzard white Biszard white Biszard white Biszard white Biszard white Bisplay racin frequency (hortzontal) Up to 86 kt/z Display scan frequency (hortzontal) Up to 86 kt/z Display features Anti-glare; Language selection; LED backlights; On-screen controls; Plug and Play; User programmable; AMD FreeSync™ Display Input Type 1 VGA, 2 HDM 1.4 Physical security features Security lock-ready ³ Management software HP Display Assistant Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights ² Energy efficiency Energy efficiency Energy efficiency (ass. A+; On-mode power consumption: 22 W; Annual energy consumption: 32 kWh ² ; Standby; 0.2 1 W; Power consumption Gon-mode; 22 W; Power consumption (formable): 0.17 W Display User Control Options Birghtness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power control; OK; Volume * Product dimensions 6118 x 604 x 4.44 39 cm Weight 3.74 kg; Posked: 5.55 kg 3.23 kg; Posked: 5.55 kg 3.23 kg; Posked: 5.55 kg 3.23 kg; Posked: 5.25 kg 3.24 kg; Posked: 5.55 kg 3.25 kg; Posked: 5.55 kg 3.26 kg; Posked: 7.22 kg; Power consumption (Grade): CSA-NRTL: EAC; Energy Star; ES7: 0: E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N No. 201; (ESS; RC G99501999; IS 1121; ISC; (S9 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS; IEC Power supply Input voltage: 100 to 204 VAC Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty Whats in the box A C power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Node: 100; PSB; RCC CCC; CCC Contraction; PDMI cable; Power adapter; QSP; CD 4 Country of origin Node: 100; PSB; RCCC; CCC Contraction; PDMI cable; Power adapter; QSP; CD 4	Tilt	Tilt: -5 to +25°
Contrast ratio 1000:1 static; 10000000:1 dynamic 1 Product color Blizzard white 1024 x 768; 1280 x 1024; 1280 x 720; 1280 x 800; 1366 x 768; 1440 x 900; 1600 x 900; 1690 x 1050; 1920 x 1080; 640 x 480; 720 x 400; 800 x 600 Display scan frequency (horizontal) Up to 86 kHz Display scan frequency (vertical) Up to 75 Hz Display features Anti-glare; Language selection; LED backlights; On-screen controls; Plug and Play; User programmable; AMD FreeSync TM Display input Type 1 VGA; 2 HDMI 1.4 Physical security features Security lock-ready 3 Management software HP Display Assistant Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights 2 Energy efficiency Energy efficiency Energy efficiency (ass. A+; On-mode power consumption 22 W; Annual energy consumption: 32 kWh ² ; Standby; O.21 W; Power consumption (on-model: 22 W; Power consumption (on-model: 0.17 W) Display User Control Options Brightness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power control; OV; Volume + (OV) Volume	Response time	5 ms gray to gray (with overdrive) ¹
Product color Bilizzard white Resolutions supported 1024 x 168 i 1280 x 1024; 1280 x 720; 1280 x 800; 1366 x 768; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 640 x 480; 720 x 400; Bisplay scan frequency (horizontal) Up to 86 kHz Display scan frequency (vertical) Up to 75 Hz Anti-glare; Language selection; LED backlights; On-screen controls; Plug and Play; User programmable; AMD FreeSync™ Display freatures Anti-glare; Language selection; LED backlights; On-screen controls; Plug and Play; User programmable; AMD FreeSync™ Display freatures Security lock-ready ³ Management software HP Display Assistant Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights ² Energy efficiency Energy efficiency (abss. 4*, On-mode power consumption 22 W; Annual energy consumption: 32 kWh ⁶ ; Standby: 0.21 W; Power consumption (on-mode): 2.2 W; Power consumption (of-mode): 0.17 W Display User Control Options Brightness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power consumption (of-mode): 0.17 W Weight 3.74 kg; Packed: 5.55 kg 8.23 lib; Packed: 12.23 lb Operating temperature range 5 to 35°C Operating temperature range 41 to 95°F Operating temperature range 5 to 35°C Operating temperature range 5 to 35°C Operating temperature range 6 to 10.8 x 20.44 x 44.93 cm BBM; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-6; FCC; GEMS; HRNN No.201; (CES.):EG 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950:1995; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950:1995; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950:1995; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950:1995; IS 1121;	Brightness	300 cd/m ² ¹
10.24 x 768 1280 x 10.24 ; 1280 x 720 ; 1280 x 800 ; 1366 x 768 ; 1440 x 900 ; 1600 x 900 ; 1680 x 1050 ; 1920 x 1080 ; 640 x 480 ; 720 x 400 ; 800 x 600	Contrast ratio	1000:1 static; 10000000:1 dynamic ¹
Book ≤ 600	Product color	Blizzard white
Display scan frequency (vertical) Display features Anti-glare; Language selection; LED backlights; On-screen controls; Plug and Play; User programmable; AMD FreeSync™ Display Input Type 1 VGA; 2 HDMI 1.4 Physical security features Security lock-ready ³ Management software HP Display Assistant Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights ² Energy efficiency En	Resolutions supported	
Display features Anti-glare; Language selection; LED backlights; On-screen controls; Plug and Play; User programmable; AMD FreeSync™ Display Input Type 1 VGA; 2 HDMI 1.4 Physical security features Security lock-ready ³ Management software HP Display Assistant Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights ² Energy efficiency (ass; A+; On-mode power consumption: 22 W; Annual energy consumption: 32 kWh5; Standby: 0.21 W; Power consumption (on-mode): 22 W; Power consumption (off-mode): 0.17 W Display User Control Options Brightness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power consumption (on-mode): 22 W; Volume +; Vol	Display scan frequency (horizontal)	Up to 86 kHz
Display input Type 1 VGA; 2 HDMI 1.4 Physical security features Security lock-ready ³ Management software HP Display Assistant Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights ² Energy efficiency Energy efficiency (abss. As; On-mode) power consumption; 22 W; Annual energy consumption; 32 kWh ⁵ ; Standby; 0.21 W; Power consumption Display User Control Options Brightness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power control; QV; Volume -; Volume + Product dimensions 61.18 x 20.44 x 44.93 cm Weight 3.74 kg; Packed: 12.23 lb Operating temperature range 5 to 35°C Operating temperature range 41 to 95°F Operating humidity range 20 to 80% RH SSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N N2.01; ICES; EC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low Diue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC Power supply Input volume 1 to 940 Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD ⁴ Country of origin Made in China Product number 4 TB31AA	Display scan frequency (vertical)	Up to 75 Hz
Physical security features Security lock-ready 3 Management software HP Display Assistant Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights 2 Energy efficiency Energy efficiency class: A+; On-mode power consumption: 22 W; Annual energy consumption: 32 kWh5; Standby: 0.21 W; Power consumption (on-mode): 22 W; Power consumption (off-mode): 0.17 W Display User Control Options Brightness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power control; OV; Volume -, Volume -, Volume - Product dimensions 61.18 x 20.44 x 44.93 cm Weight 3.74 kg; Packed: 5.55 kg 8.23 lb; Packed: 12.23 lb Operating temperature range 5 to 35°C Operating temperature range 41 to 95°F Operating humidity range 20 to 80% RH Evitifications and compliances BSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-6; FCC; GEMS; HRN N NO.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950-1; SAGO; TUV Bauart; VCI Power supply Input voltage 100 to 240 VAC Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number	Display features	Anti-glare; Language selection; LED backlights; On-screen controls; Plug and Play; User programmable; AMD FreeSync™
Management software Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights ² Energy efficiency Energy efficiency class: A+; On-mode power consumption: 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption (on-mode): 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption: 0.21 W; Power consumption: 0.22 W; Annual energy consumption: 32 kWh ⁵ ; Standby; 0.21 W; Power consumption: 0.21 W; Power consumption: 0.21 W; Power consumption: 0.21 W; Power consumption: 0.22 W; Annual energy consumption: 0.22 W;	Display Input Type	1 VGA; 2 HDMI 1.4
Environmental specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights 2 Energy efficiency Energy efficiency class: A+; On-mode power consumption: 22 W; Annual energy consumption: 32 kWh5; Standby; O.21 W; Power consumption (on-mode): 22 W; Power consumption (off-mode): 0.17 W Display User Control Options Brightness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power control; QV; Volume -; Volume +; Volume + Product dimensions 61.18 x 20.44 x 44.93 cm Weight 3.74 kg; Packed: 5.55 kg 8.23 lb; Packed: 12.23 lb Operating temperature range 5 to 35°C Operating temperature range 41 to 95°F Operating humidity range 20 to 80% RH BSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N N0.201; (EGS; JEC 60950: 1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950-1; SASO; TUV Bauart; VCCI Power supply Input voltage 100 to 240 VAC Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number 4 TB31AA	Physical security features	Security lock-ready ³
Energy efficiency Energy efficiency class: A+; On-mode power consumption: 22 W; Annual energy consumption: 32 kWh ⁵ ; Standby: 0.21 W; Power consumption (on-mode): 22 W; Power consumption (off-mode): 0.17 W Display User Control Options Brightness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power control; OV; Volume +	Management software	HP Display Assistant
Display User Control Options Brightness; Color control; Contrast; Exit; Image control; Information; Input control; Language; Management; Menu; Menu control; OK; Power control; OV; Volume -; Volume + Product dimensions 61.18 x 20.44 x 44.93 cm Weight 3.74 kg; Packed: 5.55 kg 8.23 lb; Packed: 12.23 lb Operating temperature range Operating temperature range 41 to 95°F Operating humidity range 20 to 80% RH BSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950-1; SASO; TUV Bauart; VCCI Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number 4TB31AA	Environmental specifications	Arsenic-free display glass; Low halogen; Mercury-free display backlights ²
Product dimensions 61.18 x 20.44 x 44.93 cm 3.74 kg; Packed: 5.55 kg 8.23 lb; Packed: 12.23 lb Operating temperature range 5 to 35°C Operating temperature range 41 to 95°F Operating humidity range 20 to 80% RH BSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IEC 60950: 1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950: 1; SASO; TUV Bauart; VCCI Power supply Input voltage 100 to 240 VAC Multimedia Audio-in/Audio-out, 1.5 W Speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD ⁴ Country of origin Made in China Product number 4TB31AA	Energy efficiency	
Weight3.74 kg; Packed: 5.55 kg 8.23 lb; Packed: 12.23 lbOperating temperature range5 to 35°COperating temperature range41 to 95°FOperating humidity range20 to 80% RHCertifications and compliancesBSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N NO.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IECPower supplyInput voltage 100 to 240 VACMultimediaAudio-in/Audio-out, 1.5 W speakersWarranty1 year limited warrantyWhat's in the boxAC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4Country of originMade in ChinaProduct number4TB31AA	Display User Control Options	
8.23 lb; Packed: 12.23 lb Operating temperature range 5 to 35°C Operating temperature range 41 to 95°F Operating humidity range 20 to 80% RH Certifications and compliances BSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauart; VCCI Power supply Input voltage 100 to 240 VAC Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number 4TB31AA	Product dimensions	61.18 x 20.44 x 44.93 cm
Operating temperature range 41 to 95°F Operating humidity range 20 to 80% RH Exertifications and compliances BSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950-1; SASO; TUV Bauart; VCCI Power supply Input voltage 100 to 240 VAC Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD ⁴ Country of origin Made in China Product number 4TB31AA	Weight	
Operating humidity range 20 to 80% RH BSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauart; VCCI Power supply Input voltage 100 to 240 VAC Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number 4TB31AA	Operating temperature range	5 to 35℃
BSMI; CB; CCC; CE; China Energy Label (CEL) Grade 1; CSA-NRTL; EAC; Energy Star; ES7.0; E-standby; EUP Lot-26; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950-1; SASO; TUV Bauart; VCCI Power supply Input voltage 100 to 240 VAC Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number 4TB31AA	Operating temperature range	41 to 95°F
Certifications and compliances N0.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC 60950-1; SASO; TUV Bauart; VCCI Power supply Input voltage 100 to 240 VAC Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number 4TB31AA	Operating humidity range	20 to 80% RH
Multimedia Audio-in/Audio-out, 1.5 W speakers Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number 4TB31AA	Certifications and compliances	NO.201; ICES; IEC 60950:1999; IS 1121; ISC; ISO 9241-307; KC/KCC; Low blue light; MEPS; Microsoft WHQL Certification; PSB; RCM; SABS IEC
Warranty 1 year limited warranty What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD 4 Country of origin Made in China Product number 4TB31AA	Power supply	Input voltage 100 to 240 VAC
What's in the box AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD ⁴ Country of origin Made in China Product number 4TB31AA	Multimedia	Audio-in/Audio-out, 1.5 W speakers
Country of origin Made in China Product number 4TB31AA	Warranty	1 year limited warranty
Product number 4TB31AA	What's in the box	AC power cord; Documentation; HDMI cable; Power adapter; QSP; CD ⁴
	Country of origin	Made in China
Ordering info 193015096875	Product number	4TB31AA
	Ordering info	193015096875





¹ All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower.

2 External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

3 Lock is sold separately.

4 No CD for NA region.