

AMG2016

48-55V_{DC}, 60W Power Supply




Industrial Ethernet Solutions

The AMG2016 Power Supply is a 48-55V_{DC}, 60W PoE/PoE+ Power Supply which is suitable for all AMG9000 Industrial Ethernet Media Converters with PoE.



PSU 60W
48-55VDC



Temp
-10~+71°C



Mounting
DIN

[AMG2016]

/ OVERVIEW

AC - DC DIN Rail mountable 60W Class 2 Output.

/ FEATURES

- AC/DC Power Module
- Universal Input 85~264V_{AC}
- High Efficiency - up to 89%
- Short Circuit Protection
- Internal Input Filter
- DIN Rail Mountable

Specifications.

All specifications typical at nominal line full load, 25°C unless otherwise noted.

General.

Characteristics	Conditions	Min	Typ.	Max
Isolation Voltage	Input/Output	3000V _{AC}		
Isolation Resistance	Input/Output @500V _{DC}	100MΩ		
Ambient Temperature	Operating at Vi nom.	-10		+71°C
Derating	Vi nom from +61°C to +71°C			2.5%/°C
Storage Temperature	N on operational	-25		+85°C
Relative Humidity	Vi nom, Io nom	20		90% RH
Dimension (W x D x H)	40.5 x 115 x 90 mm			
Cooling	Free air convection			
Case Material	Plastic			

Input Specifications.

Characteristics	Conditions	Min	Typ.	Max
Rated Input Voltage	IO nom	100		240V _{AC}
Input Voltage Range	Ta min... Ta max	AC in 85		264V _{AC}
	IO nom	DC in 90		375V _{DC}
Line Frequency	Vi nom, IO nom	47		63Hz
Inrush Current	IO nom	Vi: 115V _{AC}		30A
		Vi: 230V _{AC}		60A

Output Specifications.

Characteristics	Conditions	Min	Typ.	Max
Output Voltage Accuracy	Vi nom, IO min...Io nom			±1%
Minimum Load	Vi nom	0%		
Line Regulation	IO nom, Vi min...Vi max			0.5%
Load Regulation	Vi nom, IO min...Io nom			0.5%
Turn On Time	After AC is applied to Input at full resistive load			1000ms
Voltage Fall Time	IO nom, Vo = 95% ~ 10% rated voltage			150ms
Voltage Rise Time	At full resistive load			150ms
Hold Up Time	Vi = 115VAC, IO nom	20ms		
	Vi = 230VAC, IO nom	30ms		
Ripple & Noise	Vi nom, IO nom, BW=20MHz			50mV
Voltage Trim Range	Vi nom, Wo = 60W max	48		55V _{DC}
DC On Indicator Threshold at Start Up	Vi nom, IO nom	37V _{DC}		
Efficiency	Vi nom, IO nom, Po/Pi	86%		89%

Specifications.

Control and Protection.

Characteristics	Conditions	Min	Typ.	Max
Rated Over Load Protection	Vi nom	110		150%
Over Voltage Protection	Vi nom, IO nom	60		66V _{DC}
Output Short Circuit	Vi nom	Fold Forward		

Approvals and Standards.

UL / cUL	UL508 Listed
TUV	UL1310 Class 2 Power Supply (5V, 12V w/o class 2), UL60950-1 Recognised
CE	EN60950-1
	EN61000-6-3, EN55022 Class B
	EN61000-3-2, EN61000-3-3
	EN61000-6-2, EN55024, EN61000-4-2, EN61000-4-3, EN61000-4-4,
	EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11

Part Numbers.

AMG2016	48V-56V _{DC} , 60W, DIN-Rail mounting, -10°C to +61°C, power derated between 61°C & 71°C
---------	---

Notes.

