

Indoor Housing



PIH-5020



PIH-5040S

Outdoor Housing



PIH-5030



PIH-5040



PIH-5063



PIH-5084

| Model No. | Mounting | Construction | Window Dimension (mm) / Glass Thickness | Dimension (mm) | Weight | Ext. Model |
|-----------|----------|--------------|---|---|--------|---|
| PIH-5020 | Bottom | Aluminum | 84 (W) x 60 (H) / 5mm | 124 (W) x 95 (H) x 395 (D) | 1.22Kg | |
| PIH-5030 | Bottom | Aluminum | 84 (W) x 60 (H) / 5mm | 142 (W) x 104 (H) x 386 (D) | 2.5Kg | PIH-5030H (Heater) PIH-5030B (Blower) PIH-5030HB (Heater & Blower) |
| PIH-5040 | Bottom | Aluminum | 84 (W) x 60 (H) / 5mm | 142 (W) x 104 (H) x 386 (D) | 2.0Kg | |
| PIH-5040S | Bottom | Aluminum | 74 (W) x 64 (H) / 5mm | 140 (W) x 115 (H) x 373 (D) | 1.3Kg | |
| PIH-5063 | Bottom | Aluminum | Ø110 Heat Resistant Glass / 5mm | Housing : Ø134 x 318mm (L) Bracket : 211.5mm (L) | 2.0Kg | PIH5063: AC230V (Heater & Blower) PIH5064: AC24V (Heater & Blower) PIH-5067: AC117V (Heater & Blower) |
| PIH-5084 | Bottom | Aluminum | Ø78 Heat Resistant Glass / 3mm | Housing : Ø112 x 384mm (L) Bracket : 211.5mm (L) | 1.9Kg | PIH5084: AC24V (Heater) PIH-5088: AC90~260V (Heater) |

Outdoor Dome Housing

The PIH-510 series is IP68 rated camera outdoor dome housing. Designed to house a single LiLin's fast dome (PTZ) camera. This decorative housing features a flame resistant ABS top dome and a vandal resistant polycarbonate lower cover. Providing camera complete protection from vandalism. It is available in three models; wall mounting (PIH-510L), Pendant mounting (PIH-510H) and Swan Neck (PIH-510G). All models come with built-in heater and fan.



PIH-510H
PIH-510HIP

PIH-510L
PIH-510LIP

PIH-510G
PIH-510GIP

FEATURES

- Sealed to protect internal camera from moisture and dust
- Meet CE/IP68 Rated standard
- Built-in heater and fan to maintain operation temperature
- Heavy-duty construction provides complete protection from vandalism
- Bracket: Aluminum, Silver Gray
- Top Dome: Flame Resistant ABS
- Internal Fixing: Steel
- Lower Dome: Polycarbonate (clear or tinted)
- Extension Tube: PIH-Z6 (30cm)

PIH-510 Outdoor Dome Housing

| Model No. | PIH-510G PIH-510GIP | PIH-510H PIH-510HIP | PIH-510L PIH-510LIP | |
|-------------------|--------------------------------|------------------------|------------------------|--------|
| Type | Swan Neck | Pendant Mount | Wall Mount | |
| Heater Activation | On: >15°C Off: <25°C | | | |
| Fan Activation | On: >35°C Off: <25°C | | | |
| Operating Temp. | -30°F ~ +50°F (-22°F ~ +122°F) | | | |
| Input Voltage | DC 12V | | | |
| Dimension (mm) | Total Height | 875 | 477.5 | 367.15 |
| | Total Width | 685 | 274 | 405 |
| | Dome (Ø) | 270 | 270 | 270 |
| | Base (Ø) | 180 | | |
| Weight | 10Kg | 4.8Kg | 5Kg | |

Bracket



| | Model No. | Adjustment | Maximum Load | Construction | Dimension(mm) | Weight |
|-----------------|-------------|------------------------|--------------|-------------------------------|---------------------------|--------|
| Camera Bracket | PIH-500 | Pan - 360° Tilt - ±90° | 2Kg | ABS Injection | 76 (W) x 153 (H) x 73 (D) | 80g |
| | PIH-500L | Pan - 360° Tilt - ±90° | 2Kg | ABS Injection | 76 (W) x 218 (H) x 73 (D) | 100g |
| | PIH-5001N | Pan - 360° Tilt - ±90° | 2Kg | Aluminum | 123 (L) x 45 (ø) | 110g |
| | PIH-5005M | Pan - 360° Tilt - ±90° | 5Kg | Aluminum | 164 (L) x 119 (ø) | 280g |
| | PIH-5004 | Pan & Tilt | 10Kg | Aluminum, Light Gray Textured | 85 (W) x 309 (H) x 99 (D) | 600g |
| | PIH-5004L | Pan & Tilt | 10Kg | Aluminum, Light Gray Textured | 61 (W) x 240 (H) x 83 (D) | 300g |
| | PIH-5004LBK | Pan & Tilt | 10Kg | Aluminum, Black Textured | 61 (W) x 240 (H) x 83 (D) | 300g |
| Scanner Bracket | PIH-5003 | Pan | 10Kg | Aluminum, Light Gray Textured | 85 (W) x 309 (H) x 99 (D) | 450g |



| | Model No. | Maximum Load | Construction | Dimension(mm) | Weight |
|-----------------|------------|--------------|---|-----------------------------|--------|
| Outdoor Bracket | PIH-301B | 30Kg | Steel, Silver Gray Baked Enamel Finish | 248 (W) x 470 (H) x 200 (D) | 3600g |
| | PIH-303B | 30Kg | Aluminum, Light Gray Textured | 148 (W) x 385 (H) x 175 (D) | 1200g |
| | PIH-303P | 30Kg | Aluminum, Light Gray Textured | 148 (W) x 335 (H) x 175 (D) | 1100g |
| Extension Tube | PIH-303PEX | - | Aluminum, Light Gray Textured | 300(H) | - |
| Pilot Head | PIH-301BH | 15Kg | Aluminum, Silver Gray Baked Enamel Finish | 177 (W) x 109 (H) x 106 (D) | 800g |
| Camera Bracket | PIH-WM | 5Kg | Aluminum, Creamy Whie Textured | 132 (W) x 111 (H) x 169 (D) | 600g |

PIH-510CPM Outdoor Corner & Pole Mount



PIH-510CPM

Maximum Load : 25Kg
 Construction : Aluminum, Light Gray Textured
 Strap : Stainless Strap for Pole x 2
 Diameter Range 2.5~7 inch
 Dimension(mm) : 275(W) x 91 (H) x 182 (D)
 Weight : 500g

PIH-303BX Indoor Bracket for Fast Dome



PIH-303BX

Maximum Load : 30 Kg
 Construction : Steel, Light Gray Textured
 Dimension(mm) : 180(W) x 318.5(H) x 214(D)
 Weight : 3900g