



M155v Messenger

The ultimate messaging device for environments like healthcare and hospitality

At a Glance

- Appealing design, easy to use
- Increased accessibility
- Flexibility, comfort and mobility
- Messaging and voice -communications in one
- Personal alarm function
- Reduced communication and maintenance costs
- A simple, small and secure solution

The M155v Messenger is a sophisticated wireless messaging device for use in professional healthcare and hospitality environments. The small watch-like device is easy to wear and provides the mobile user the optimum in mobility, accessibility, flexibility and comfort. Besides a messaging device, the M155v also offers the mobile user speaker-phone communication and acts as a personal alarm device.

The M155v Messenger brings mobile messaging and speakerphone -communication for DECT users to the highest level of comfort, with:

- An appealing design
- Three-line display
- Easy to carry (on wrist or as necklace)
- Easy to use
- Gives users full control over their accessibility
- Provides various call control options and integrates seamlessly with the PBX and (messaging) applications

Empowered by Innovation

NEC

- Complies with DECT standards for high quality speech and security (DECT authentication)
- Provides an excellent communications device for organizations that rely on messaging or alarm information sent to employees, such as in hospitals and hotel environments
- Is easy to service and maintain

Integrated with applications common in healthcare and hospitality, the M155v DECT Messenger meets the needs of message communications in environments where conveying messages to the mobile user is of utmost importance.

The M155v Messenger can furthermore be used for voice communication and serves as a personal alarm device.



Features

Features M155v Messenger		
Call handling features	• Calls to preconfigured destinations only	• CLI (number and name): when presented by the system
	• Immediate emergency (SOS) call set up	• Talk time: 8 hours
	• Standby time: 80 hours	
Design	• Light, small ergonomic design: Optimized for comfort and ease of use as a messaging device, styled for professional environments	
Directory	• Emergency number	• Personal phone book with 5 entries
Display	• 3 line display for 42 characters	• Illuminated display: On incoming calls and message
	• Date/time indication: Based upon PBX clock	
Keys	• Operated by two keys only	
Localization	• Multiple supported languages: 5	• Dual frequency band
Menu	• Easy menu (for limited settings only)	
Messaging	• Messaging (LRMS) support	• Message broadcast support (receiving)
	• Use of predefined set of messages (normal priority only): 5	• Support of different priorities for incoming messages: Normal, urgent and emergency
Mobility/other	• Single subscription to DECT system	
Sound/Audio	• Adjustable ringer melody: 12	• Coverage warning
	• Loudspeaker mode/hands free mode only	• Vibrator Mode
	• Silent mode	
Security	• Automatic encryption for secure calls	
Service/maintenance	• Software upgrading via air interface ¹⁾	• Configurable by easy to use Configurator application
User interface	• Distinctive melodies for messages and priorities	• Status line indicators in the display
1) The DECT system to which the M155v Messenger is subscribed, should be able to support "software downloading over the air". Note that the M155v Messenger cannot be upgraded by any other means.		

Technical Data

Memory

Storage capacity for:

- 1 emergency entry (number and optionally a message)
- 5 additional phonebook entries
- 5 predefined (reply) messages

Physical characteristics

Dimensions

Messenger: 55x43x17 mm

Charger: 95x58x20 mm

Weight

Messenger: 36 g

Charger & AC Adapter: 244 g

Protection

Messenger: IP20

Range

Indoor: 50 m max ²⁾

Outdoor: 300 m max ²⁾

Power Supply

Messenger: 3.7V, 400mAh Li-Polymer battery (non-replaceable).

Charger: Powered via attached AC/DC adapter

Input: 100-240VAC/50/60Hz/150mA

Output: 5VDC/350mA

Mains plug: ³⁾ Euro, UK, North America or Australia

Colour and Finishing

Messenger:

- Keys and rim around display: silver, non-gloss
- Body: black, non-gloss

Desktop Charger and AC Adapter:

- Desktop Charger: White, non-gloss
- AC Adapter: Black, non-gloss

²⁾ The range of the M155v Messenger depends on the environment and presence of obstacles

³⁾ The mains plug contains a changeable part for the different power plugs

Audible indicators

- Charger warning

Status line indicators

Status line indicators in the display are:

- Battery condition
- Field strength
- New message
- Phone book
- Ringing/Off hook
- Silent (Ringer and notification off)

Supported Menu languages

The M155v Messenger supports 5 selectable languages: English, French, German, Italian and Spanish

Package content

M155v Package contents

- | | |
|-------------------|-----------------------------|
| • M155v Messenger | • Wrist strap |
| • Neck strap | • Reference guide (English) |

Accessories

M155v Messenger Accessories

- Desktop charger and attached adapter

Environmental conditions

Temperature Range	
Operating:	0°C to +40°C
Transport:	-25°C to +70°C
Storage:	-5°C to +45°C
Relative Humidity	
Operating:	10 to 95%
Transport:	10 to 100%
Storage:	10 to 95%

Compliance

Compliance M155v Messenger	
The M155v Messenger carries a CE mark	
EMC:	EN301-489-1, EN301 489-6
EMF:	EN50360: 2001
DECT:	EN301 406, EN300 175 EN 300 444
Safety:	EN 60950-1

Directives and regulations

Directives and regulations Europe	
R&TTE directive 1999/5/EC	
EMC directive 2004/108/EC	
LVD directive 2006/95/EC	
ROHS directive 2002/95/EC and WEEE directive 2002/96/EC	
ERP directive 2009/125/EC EC implementing measures 1275/2008 and 278/2009	

Directives and regulations North America	
FCC part 15C, 15D	
RSS 210, RSS 213	
HAC/VC	

Transmission

Transmission and frequency	
Average Radio RF power ⁴⁾:	10 mW
Frequency band EMEA ⁵⁾:	1880 - 1900 MHz
Frequency band Latin America ⁵⁾:	1910 - 1930 MHz
Frequency band North America ⁵⁾:	1920 - 1930 MHz
⁴⁾ The transmitted Radio RF power is according to local regulations. ⁵⁾ The frequency band is automatically selected by the M155v Messenger based on the frequency band used by the DECT system.	

UNIVERGE®360 is NEC's approach to unifying business communications. It places people at the center of communications and delivers on an organization's needs by uniting infrastructure, communications and business.



About NEC Corporation: NEC Corporation (NASDAQ: NIPNY) is one of the world's leading providers of Internet, broadband network and enterprise business solutions dedicated to meeting the specialized needs of its diverse and global base of customers. NEC delivers tailored solutions in the key fields of computer, networking and electron devices, by integrating its technical strengths in IT and Networks, and by providing advanced semiconductor solutions through NEC Electronics Corporation. The NEC Group employs more than 150,000 people worldwide. For additional information, please visit the NEC home page at: <http://www.nec.com>

For further information please contact your local NEC representative or:

EMEA (Europe, Middle East, Africa)
NEC Unified Solutions
www.nec-unified.com

North America (USA)
NEC Corporation of America
www.necam.com

Corporate Headquarters (Japan)
NEC Corporation
www.nec.com

Empowered by Innovation

NEC