



RocketRAID 2700 Series

PCI-E 2.0 x8/x16 6Gb/s SAS/SATA RAID HBA's



The Industry's Most Cost-Effective, Comprehensive Selection of SAS/SATA 6Gb/s RAID HBA's

HighPoint RocketRAID 2700 HBA's are the most diverse, versatile and cost-effective RAID HBA's available in today's marketplace. Powered by our industry-proven RAID technology, industry-standard Mini-SAS connectivity with support for up to 32 devices and PCI-Express 2.0 x8 and x16 bus speeds, RocketRAID 2700 HBA's can be easily integrated into a variety of hardware and software platforms, and are ideal for cost-effective, high-density SMB applications.

HighPoint RAID Technology

For over a decade, HighPoint has strived to take the cost and complexity out of RAID. HighPoint was the first to introduce affordable RAID 5 solutions to the storage marketplace, for both SMB and consumer applications. Our industry-proven Value-RAID technology keeps costs in check by fully utilizing available system resources in order to optimize data transfer and security, and supports a wide-range of storage configurations including RAID 0, 1, 5, 6, 10, 50 and JBOD.

Wide Selection of RAID HBA Configurations

Powered by industry-standard Mini-SAS connectivity with support for up to 32 devices, and PCI-Express 2.0 x8 and x16 bus speeds, RocketRAID 2700 HBA's can be easily integrated into a variety of hardware and software platforms, and are ideal for cost-effective, high-density SMB applications.

Complete, Flexible Upgrade Paths

RocketRAID 2700 HBA's are fully backwards compatible with SAS/SATA 3Gb/s devices, PCI-Express 1.0 and 2.0 motherboards, and are compliant with all major operating systems including Windows, Linux, FreeBSD & Mac OS X.

RAID arrays can be freely moved to any other RocketRAID 2700 HBA. Upgrading, scaling and expanding storage has never been easier.

Comprehensive RAID & Storage Management Interface

The streamlined web-based user interface simplifies the storage configuration process and allows customers to quickly assess total available capacity, the status of individual hard drives or SSD's, and the health of storage configurations. Optional auto rebuild and hot spare features add additional layers of data security to redundant RAID 5 and 6 configurations. Administrators can designate unused drives to automatically take the place of failed units or configure the RocketRAID HBA to immediately initialize rebuild process by simply plugging in a new drive.

Feature Highlights




- HighPoint Turbo RAID Technology: RAID 0, 1, 5, 6, 10, 50 JBOD
- Wide Selection of HBA RAID Configurations: 4-32 Ports
- Complete, Flexible Upgrade Paths
- Comprehensive RAID & Storage Management Interface



Advanced management features allow customers to manage storage remotely via an internet connection or local network, and configure Email notification to inform one or more users of changing storage conditions while outside of the work environment. In addition, optional CLI packages are available for Linux and FreeBSD platforms.

RocketRAID 2700 PCIe x8 RAID Controllers Feature Specifications

Port Type	RocketRAID 2720SGL - 2x SFF-8087 (Mini-SAS) RocketRAID 2710 - 1x SFF-8087 (Mini-SAS) RocketRAID 2722 - 2x SFF-8088 (Mini-SAS) RocketRAID 2711 - 1x SFF-8088 (Mini-SAS) RocketRAID 2721 - 1x SFF-8087&1x SFF-8088 (Mini-SAS)
Number of Channel / Port	RocketRAID 272x -8x 6Gb/s SAS/SATA Channels RocketRAID 271x -4x 6Gb/s SAS/SATA Channels
Number of Devices	RocketRAID 272x: 8x SAS /SATA Hard Drive or SSD / 2x SAS LTO devices RocketRAID 271x: 4x SAS /SATA Hard Drive or SSD / 1x SAS LTO devices
Bus Interface	PCIe 2.0 x8
Form Factor	Low Profile
Dimensions	RocketRAID 2720SGL/2710 -96.3mm*65mm / RocketRAID 2722/2711/2721 - 120mm*68mm
Weight	RocketRAID 2720SGL - 0.12lb RocketRAID 2710 - 0.11lb RocketRAID 2722 - 0.19lb RocketRAID 2711 - 0.18lb RocketRAID 2721 - 0.18lb
RAID Mode	0, 1, 5, 6(1), 10, 50 and JBOD / Non-RAID Mode
Operating System	Window Server 2008 and Window 7 and later
	Linux: RedHat Enterprise, Open SuSE, Fedora Core, Debian, Ubuntu
	FreeBSD
	Driver embedded into FreeBSD 9.0 and later
	Mac OS X 10.6 and later Driver embedded into Mac OS X 10.8 and later
Advanced RAID Features	
Flash ROM for Upgradeable BIOS	Yes
Storage Health Inspector	Yes
Redundant RAID Configurations	Yes
BIOS PnP (plug and play) and BBS (BIOS boot specification) support	Yes: RocketRAID 2720SGL, 2710
Bootable RAID Array	Yes
EFI for Mac Platform	Yes
Multiple RAID Partitions supported	Supports up to 4 RAID partition per disk
Storage Configurations Support Details	Direct Attached
Multiple RAID Adapters supported	Supports up to 4 RAID controllers per system
Online Array Roaming	Yes
Online RAID Level Migration (ORLM)	Yes
Online Capacity Expansion (OCE)	Yes
RAID Initialization Background/Foreground/Quick	Yes
Global Hot Spare Disk support	Yes
Automatic and configurable RAID Rebuilding Priority	Yes
Disk Format compatible: 512, 512e, 4Kn	Yes
Larger than 2 TB Drive and RAID Array support	Yes
Spin down Massive Arrays of Idle Disks support	Yes
Native Command Queuing	Yes
Staggered Drive Spin Up	Yes
Write Back and Write Through	Yes

RAID Monitoring and Management Suite	
RAID Monitoring and Management Suite	RAID Management Suites: BIOS/Firmware configuration tool Browser-Based management tool CLI (Command Line Interface- scriptable configuration tool) API package
Enclosure Management Interface: SGPIO, SES-2 and I2C (Drive LEDs supported: SGPIO, SES-2 and LED Header)	Yes, except RocketRAID 2711, RocketRAID 2722 only support via SES
SMTP Email Alert Notification	Yes
Alarm Buzzer	Yes
Operating Environment	
Work Temp:	+5°C ~+ 55°C
Storage Temp:	-20°C ~ +80°C
Relative Humidity:	5% ~ 60% non condensing
Operating Voltage:	PCI-e: 12V/3.3V Power: 11W
MTBF (Mean Time Before Failure)	920,585 Hours
Certification Approval	FCC, CE

RocketRAID 2700 PCIe x8 RAID Controllers	RocketRAID 2720SGL	RocketRAID 2722	RocketRAID 2721
Product Image			
Host bus Interface	PCI-Express 2.0 x8	PCI-Express 2.0 x8	PCI-Express 2.0 x8
Number of Device Ports	8 Internal Ports	8 External Ports	4 Internal / 4 External Ports
Form Factor	Low Profile	Low Profile	Low Profile
Retail Box Dimensions	7.76" L x 6.81" W x 1.18" H	7.76" L x 6.81" W x 1.18" H	7.76" L x 6.81" W x 2.36" H
Retail Box Weight	0.41 lbs	0.49 lbs.	0.89 lbs.
UPC Code	643653272020	643653272211	643653272112
Kit Contents	1x controller card 1x Low Profile Bracket 1x Quick Installation Guide	1x controller card 1x Low Profile Bracket 1x Quick Installation Guide	1x controller card 1x SFF8087 to SFF8087 cable 1x Low Profile Bracket 1x Quick Installation Guide

RocketRAID 2700 PCIe x8 RAID Controllers	RocketRAID 2710	RocketRAID 2711
Product Image		
Host bus Interface	PCI-Express 2.0 x8	PCI-Express 2.0 x8
Number of Device Ports	4 Internal Ports	4 External Ports
Cable Included	One Mini-SAS Cable: SFF-8087 to SFF-8087	n/a
Retail Box Dimensions	7.76" L x 6.81" W x 2.36" H	7.76" L x 6.81" W x 1.18" H
Retail Box Weight	1.18 lbs.	0.48 lbs.
UPC Code	643653271016	643653271115
Kit Contents	1x controller card 1x SFF8087 to SFF8087 cable 1x Low Profile Bracket 1x Quick Installation Guide	1x controller card 1x Low Profile Bracket 1x Quick Installation Guide