



unilan® Patch Panel CU 25/4 Cat.3 / Voice  
 unilan® Patch Panel CU 50/4 Cat.3 / Voice

Dätwyler



unilan® Patch Panel CU 25/4



unilan® Patch Panel CU 50/4

## Product information

### unilan® Patch Panel CU 25/4 and CU 50/4 Cat.3, Voice

#### Application

For the transmission of digital (ISDN) and analogue voice signals. Especially suitable for all applications of class C according to EN 50173-1 and ISO/IEC 11801. The patch panel supports cables up to 100 pairs or 50 pairs (telephone cable).

A maximum of 4 wires may be connected to a RJ45 socket.

Wiring tool is available as an accessory. It consists of 2 angled metal brackets that can be simply fastened to the 19" rack or cabinet, thus making terminations quicker and easier.

#### Construction

Chassis: Painted metal to RAL 7035, grey  
 Width: 482 mm (19")  
 Height: 44 mm (1U)  
 Depth: 129 mm

#### Connection system

Cable: IDC-termination  
 Socket: Unscreened RJ45 socket (EN 60603-7)

#### Standards

ISO/IEC 11801, EN 50173

#### Connection

2-pairs according to PIN 3-6, 4-5

Article No.	Description	Colour (similar)	PU
418 000	unilan® Patch Panel CU 25/4 with 25 x RJ45 Jacks, Cat.3, metal chassis	grey, RAL 7035	1 piece
418 001	unilan® Patch Panel CU 50/4 with 50 x RJ45 Jacks, Cat.3, metal chassis	grey, RAL 7035	1 piece
418 002	unilan® Patch Panel CU 25/4 with 25 x RJ45 Jacks, Cat.3, metal chassis	black, RAL 9005	1 piece
418 003	unilan® Patch Panel CU 25/4 with 50 x RJ45 Jacks, Cat.3, metal chassis	black, RAL 9005	1 piece

#### Accessories

Article No.	Description	PU
1401 624	Patch panel wiring tool	1 set
1401 609	IDC termination tool	1 piece
185 896	unilan® Punch Down Tool 110	1 piece